

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 8 W.

CHAINS	<p>N. $0^{\circ} 10'$ E., on the E. bdy. of sec. 24.</p> <p>Descend 260 ft. over broken NW. slope, through heavy timber and dense undergrowth.</p> <p>26.65 Creek, 1 lk. wide, course N. 80° W.; asc. 55 ft. over SW. slope.</p> <p>29.70 Spur, slopes NW.; desc. 55 ft. over broken NW. slope.</p> <p>37.05 Point for the $\frac{1}{4}$ sec. cor. of sec. 19 only, T 25 S., R. 7 W., at mid-point latitudinally, on W. bdy. of sec. 19.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td> </td><td>T 25 S</td></tr> <tr><td> </td><td>R 7 W</td></tr> <tr><td> </td><td>$\frac{1}{4}$ S 19</td></tr> <tr><td> </td><td>1964</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ E., 24 lks. dist., mkd. $\frac{1}{4}$ S 19 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 66° E., 70 lks. dist., mkd. X BT.</p> <p>Descend 15 ft. over broken NW. slope.</p> <p>43.40 Point for the $\frac{1}{4}$ sec. cor. of sec. 24 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td> </td><td>T 25 S</td></tr> <tr><td> </td><td>R 8 W</td></tr> <tr><td> </td><td>$\frac{1}{4}$ S 24</td></tr> <tr><td> </td><td>1964</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 44° W., 70 lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p> <p style="padding-left: 40px;">A madrone, 8 ins. diam., bears N. $41\frac{1}{2}^{\circ}$ W., 29 lks. dist. mkd. $\frac{1}{4}$ S24 BT.</p> <p>Corner falls on a spur, slopes N. 20° W.; desc. 360 ft. over N. slope.</p> <p>52.65 Dry creek bed, 3 lks. wide, drains N. 75° W.; asc. 315 ft. over broken SW. slope.</p> <p>74.10 True point for the closing corner of secs. 18 and 19, T. 25 S., R. 7 W., hereinafter described.</p> <p>Ascend 95 ft. over broken SW. slope.</p> <p>80.50 Top of ascent, slopes W.; desc. 40 ft. over N. slope.</p> <p>86.80 The cor. of secs. 13 and 24 only, determined at record bearing and distance from the remaining original bearing trees:</p> <p style="padding-left: 40px;">A down fir, 25 ins. diam., bears S. 82° E., 19 lks. dist., no marks visible.</p>		T 25 S		R 7 W		$\frac{1}{4}$ S 19		1964		T 25 S		R 8 W		$\frac{1}{4}$ S 24		1964
	T 25 S																
	R 7 W																
	$\frac{1}{4}$ S 19																
	1964																
	T 25 S																
	R 8 W																
	$\frac{1}{4}$ S 24																
	1964																