

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 8 W.

CHAINS

A white fir snag, 16 ins. diam., bears N. 85° W.,
8 33 lks. dist., with scribe marks T25S R8W BT
visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in
the ground, with brass cap mkd.

T 25 S		
R 8 W		R 7 W
S 13		S 18
S 24		
1964		

from which new bearing trees

A white fir, 27 ins. diam., bears S. 75° W., 50½
lks. dist., mkd. T25S R8W S24 BT.

A fir, 45 ins. diam., bears N. 35° W., 50 lks.
dist., mkd. T25S R8W S13 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, white fir, madrone, alder,
dogwood, yew, oak, and maple; undergrowth, vine maple,
salal, ocean spray, hazel, Oregon grape, poison oak, manzanita,
rhododendron, huckleberry, and blackberry.

N. 0° 15' E., on the E. bdy. of sec. 13.

Descend 75 ft. over N. slope, changing to NW. slope,
through heavy timber and dense undergrowth.

12.00 Spur, slopes N. 30° W.; desc. 160 ft. over N. slope.

18.30 Spring, drains N. 10° E.; desc. 170 ft. over NE. slope.

27.03 Point for the ¼ sec. cor. of sec. 18 only, T25 S., R. 7 W.,
at proportionate distance latitudinally, on the W. bdy.
of sec. 18.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 25 S		
R 7 W		
¼ S 18		
1964		

from which

A fir, 28 ins. diam., bears N. 50° E., 47 lks.
dist., mkd. ¼ S18 BT.

A white fir, 15 ins. diam., bears S. 49° E.,
41½ lks. dist., mkd. ¼ S18 BT.

Descend 365 ft. over broken NE. slope.!

37.10 Creek, 4 lks. wide, course N. 40° W.; asc. 15 ft. over
S.W. slope.

37.65 Point for the ¼ sec. cor. of sec. 13 only, at proportionate
distance; there is no remaining evidence of the original corner.