

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 8 W.

CHAINS

A white fir, 16 ins. diam., bears N. 18° W., 94 lks. dist., with scribe marks T25S R8W S12 CS BT visible on double blaze.

Add marks BLM 1964 to the bottom of brass cap.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, white fir, madrone, alder, dogwood, yew, oak, and maple; undergrowth, vine maple, salal, ocean spray, hazel, Oregon grape, poison oak, manzanita, rhododendron, huckleberry, and blackberry.

N. 8° 09' W., on the E. bdy. of sec. 12.

Descend 120 ft. over broken NW. slope, through heavy timber and dense undergrowth/

7.00 Spur, slopes N. 40° W.; desc. 220 ft. over steep N. slope.

12.13 The original witness point of secs. 7 and 12, established by Dennis Hathorn, in 1857, recorded and remonumented by Claude Kerr, Registered Engineer, in 1954, with a wooden stake, 4 ins. square, 36 ins. above the ground, loosely set, marked WC 7 WC 12, 5895 chs., subsequently remonumented by Milo E. Godfrey, Deputy County Surveyor, in 1962, with an iron pipe, 1 in. diam., firmly set, 8 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

	T 25 S		
R	S	S	R
8	12	7	7
W			W
	W C		
	1962		

from which the remaining original bearing tree

A fir, 52 ins. diam., bears S. 80° E., 12½ lks. dist., with old bark blaze. (Record, 10 lks.)

and a bearing tree marked by Kerr

A cedar, 17 ins. diam., bears N. 55° W., 28½ lks. dist., with scribe marks WC S12 BT visible on partially healed double blaze.

and a bearing tree marked by Godfrey

A myrtle, 6 ins. diam., bears S. 50° E., 24½ lks. dist., mkd. T25S R7W WC S7 CS BT visible on double blaze.

Add marks BLM 1964 to bottom of brass cap.

N. 0° 24' E., beginning new measurement.

Descend 185 ft. over steep N. slope, through scattering timber and dense undergrowth.

3.25 Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.

3.57 Point for the witness cor. to the meander cor. of secs. 7 and 12.