

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R 8 W.

CHAINS

From this point, a point established by Claude Kerr, Registered Engineer, in 1954, bears S. 79° 30' W., 0.12 chs. dist., monumented with an iron pipe, 1/2 ins. diam., firmly set, protruding 12 ins. above the ground.

N. 0° 13' W., beginning new measurement.

Ascend 220 ft. over SW. slope, across open land.

1.50 County road under construction, 50 lks. wide, bears N. 60° W. and S. 60° E.

7.30 Enter heavy young timber and dense undergrowth.

15.00 Spur, slopes W.; desc. 250 ft. over NW. slope.

28.45 County road under construction, 50 lks. wide, bears N. 75° E. and S. 60° W.

30.70 Right bank of the Umpqua River, course N. 80° E.

30.84 Point for the meander cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner. The cor. point falls on the left bank of the Umpqua River on unstable ground, where it is impractical to establish a permanent monument.


Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, white fir, madrone, alder, dogwood, yew, oak, and maple; undergrowth, vine maple, salal, ocean spray, hazel, Oregon grape, poison Oak, Manzanita, rhododendron, huckleberry, and blackberry.

N. 0° 13' W., bet. secs. 1 and 6.

Ascend 30 ft. over SE slope, through heavy timber and dense undergrowth.

1.35 Point for the witness cor. to the cor. of secs. 1, 6, 7 and 12,

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A fir, 14 ins. diam., bears N. 43 1/2° E., 94 lks. dist., mkd. X BT.

A boulder, 8 x 4 x 4 ft. above ground, bears S. 27° E., 30 lks. dist., mkd. X BO.

A fir, 8 ins. diam., bears S. 31 3/4° W., 60 lks. dist., mkd. X BT.

A boulder, 3 x 2 x 2 ft. above ground, bears N. 47° W., 13 lks. dist., mkd. X BO.