

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of E. Bdy., T. 25 S., R. 8 W.

## CHAINS

- 56.25 Creek, 1 lk. wide, course S. 80° W.; asc. 55 ft. over broken SW. slope.
- 61.60 Spur, slopes S. 60° W.; asc. 55 ft. over broken SW. slope.
- 73.70 Creek, 3 lks. wide, course S. 70° W.; asc. 60 ft. over broken SW. slope.
- 78.40 Top of ascent, slopes W.; desc. 25 ft. over NW. slope.
- 79.96 The cor. of Tps. 24 and 25 S., Rs. 7 and 8 W., monumented with an iron post, 2½ ins. diam., protruding 4 ins. above ground, firmly set, with brass cap marked and witnessed as described in the official record of the 1959 remonumentation.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, white fir, madrone, alder, dogwood, yew, oak, maple, and myrtle; undergrowth, vine maple, salal, ocean spray, hazel, Oregon grape, poison oak, manzanita, rhododendron, huckleberry, and blackberry.

Dependent Resurvey of Portion of the Subdivisional Lines  
T. 25 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the 1874 survey by William H. Byars, and the  
1896 retracement and survey by William P. Heydon)

From the ¼ sec. cor. of secs. 29 and 30, perpetuated and recorded by G. G. Stewart, County Surveyor, in 1921, from the original cor. stake and one bearing tree, which are no longer in existence, monumented with an eye bolt, 1 in. diam., 2 ins. below ground, firmly set, from which a bearing tree marked by Stewart:

A sawed fir stump, rotted and burned, 24 ins. diam., bears S. 43, W., 36 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 25 S R 7 W

1  
S 30 S 29  
1964

FDOK PER NORTH CRAFT  
8/86 - 9/86 M102-79

SEE M 109 - 54 A & B  
DEC 1989

from which new bearing trees

A fir, 11 ins. diam., bears S. 74° E., 12½ lks. dist., mkd. ¼ S29 BT.

A fir, 5 ins. diam., bears S. 81° W., 25 lks. dist., mkd. X BT.

Reset eye bolt alongside the iron post.

N. 0° 31' W., bet. secs. 29 and 30, marking and blazing the true line.

Ascend 10 ft. over SE. slope, across logged area. through heavy young timber and dense undergrowth.