

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS	
36.00	Spur, slopes S. 75° E.; desc. 50 ft. over NE. slope.
38.75	Dry creek bed, 2 lks. wide, drains SE.; asc. 105 ft. over S. slope.
40.43	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron pipe, 12 ins. long, 1 in. diam., 3 ins. in drill hole in bed rock, with brass cap mkd.
	T 25 S R 7 W
	S 19 $\frac{1}{4}$ S 20
	1964
	from which
	A fir, 25 ins. diam., bears N. 60° E., 59 lks. dist., mkd. $\frac{1}{4}$ S20 BT.
	A fir, 11 ins. diam., bears S. 34 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. $\frac{1}{4}$ S19 BT.
	Ascend 75 ft. over S. slope.
42.00	Spur, slopes SE.; asc. 150 ft. over broken SE. slope.
49.50	Ravine, drains S. 25° E.; asc. 400 ft. over S. slope.
58.40	An original line tree marked by William H. Byars in 1874, a fir, 40 ins. diam., with 2 notches on N. & S. sides.
	This tree now becomes an angle point.

	N. 0° 50' W., beginning new measurement.
	Ascend 10 ft. over S. slope.
1.94	Point for the N $\frac{1}{16}$ sec. cor. of secs. 19 and 20.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N $\frac{1}{16}$
	S 19 $\frac{1}{16}$ S 20
	1964
	from which
	A fir, 15 ins. diam., bears N. 28° E., 53 lks. dist., mkd. N $\frac{1}{16}$ S20 BT.
	A fir, 12 ins. diam., bears S. 86° W., 55 lks. dist., mkd. N $\frac{1}{16}$ S19 BT.
	Corner is on the ridge, dividing Hubbard Creek and Cougar Creek drainages, bears NE. and SW.; desc. 110 ft. over broken NW. slope.
2.35	Dirt road, 15 lks. wide, bears NE. and S. 60° W.
21.85	The cor. of sec. 17, 18, 19, and 20, recorded and remonumented by James W. Byron, Deputy County Surveyor, in 1957, with an iron pipe, 1 in. diam., protruding 12 ins. above the ground, firmly set, with brass cap mkd.

Fd. OK. by
 T. SHRUM
 12-13-82
 M 93-43