

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 7 W.

CHAINS	
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T. 25 S R 7 W ¼ S 18 S 19 1964
	from which anew bearing tree
	A fir, 10 ins. diam., bears S. 10° W., 101½ lks. dist., mkd. ¼ S19 BT.
	-----
	N. 89° 42' W., beginning new measurement.
	Descend 200 ft. over W. slope, changing to broken NW. slope.
10.75	Creek, 1 lk. wide, course NW.; asc. 15 ft. over NE slope.
13.75	Spur, slopes N. 15° W.; desc. 45 ft. over SW. slope.
15.25	Ravine, drains N. 10° W.; asc. 115 ft. over NE slope
18.00	Spur, slopes N. 30° E.; asc. 10 ft. along N. slope.
18.98	Point for the W 1/16 sec. cor. of secs. 18 and 19.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 S 18 S 19 1964
	from which
	A fir, 10 ins. diam., bears N. 73° E., 24 lks. dist., mkd. W 1/16 S18 BT.
	A fir, 13 ins. diam., bears S. 53° E., 55½ lks. dist., mkd. W 1/16 S19 BT.
	Descend 5 ft. along N. slope.
21.20	Ravine, drains N. 60° E.; asc. 215 ft. over SE. slope, changing to E. slope.
28.30	Spur, slopes N. 30° W.; desc. 100 ft. over broken SW. slope.
36.88	Intersect the E. bdy. of T. 25 S., R. 8 W., and true point for the closing corner of secs. 18 and 19, T. 25 S., R. 7 W.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 S R 8 W   R 7 W S 24   S 18 CC S 19 1964
	from which
	A cedar, 20 ins. diam., bears N. 38½° E., 137 lks. dist., mkd. T25S R7W S18 CC BT.