

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

38.75

The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, determined at record bearing and distance from the remains of the original NW. bearing tree:

A fir snag, 21 ins. diam., bears N. 80° W., 16 lks. dist., mkd. $\frac{1}{4}$ S BT on a bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 25 S	R 8 W
$\frac{1}{4}$ S 25	
S 36	
1964	

from which new bearing trees

A fir, 13 ins. diam., bears N. $50\frac{3}{4}^\circ$ E., 56 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

A fir, 21 ins. diam., bears S. $49\frac{1}{4}^\circ$ E., 28 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

S. $84^\circ 34'$ W., beginning new measurement.

Ascend 255 ft. over NE. slope.

10.80

Ridge and dirt road, 15 lks. wide, bears N. and S.; desc. 115 ft. over SW. slope.

23.50

Wet ravine, drains N. 50° W.; asc. 45 ft. over NE. slope.

28.30

Spur, slopes N. 20° W.; desc. 135 ft. over SW. slope.

34.00

Creek, 1 lk. wide, course N. 20° W.; asc. 85 ft. over NE. slope.

40.51

Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

T 25 S	R 8 W
S 26	S 25
S 35	S 36
1964	

f

from which

A hemlock, 22 ins. diam., bears N. $14\frac{3}{4}^\circ$ E., 20 lks. dist., mkd. T25S R8W S25 BT.

A fir, 7 ins. diam., bears S. $67\frac{1}{2}^\circ$ E., 43 lks. dist., mkd. T25S R8W S36 BT.

A fir, 10 ins. diam., bears S. $74\frac{1}{4}^\circ$ W., 51 lks. dist., mkd. T25S R8W S35 BT.

A fir, 28 ins. diam., bears N. 70° W., 14 lks. dist., mkd. T25S R8W S26 BT.