

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

S. bdry. From this point, the cor. of secs. 1, 2, 35 and 36, on the S. bdry. of the Twp. bears S. 0° 41' E., 78.72 chs. dist., determined at the record bearing from the remains of the original BT's:

- A down fir, 38 ins. diam., bears N. 25° E., 62 lks. dist., with no marks visible.
- A chinquapin snag, 17 ins. diam., bears sS. 50° E., 21 lks. dist., with no marks visible on opened blaze.
- A fir, snag, 40 ins. diam., bears S. 50° W., 22 lks. dist., 20 lks. to face, with illegible scribe marks visible on a bark blaze. (Record, 20 lks.)
- A madrone, 22 ins. diam., bears N. 35° W., 14 lks. dist., with no marks remaining on an open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 S	R 8 W
S 35	S 36
S 2	S 1
T 26 S	R 8 W
1964	

from which new bearing trees

- A fir, 17 ins. diam., bears N. 38° E., 42 lks. dist., mkd. T25S R8W S36 BT.
- A fir, 16 ins. diam., bears S. 84¼° E., 57 lks. dist., mkd. T26S R8W S1 BT.
- A fir, 8 ins. diam. bears S. 37½° W., 84 lks. dist., mkd. T26S R8W S2 BT.
- A fir, 8 ins. diam., bears N. 30° W., 75 lks. dist., mkd. T25S R8W S35 BT.

From this same point, the ¼ sec. cor. of secs. 26 and 35, bears N. 86° 52' W., 41.04 chs. dist., determined at record bearing and distance from the original NW. bearing tree:

- A fir, 36 ins. diam., bears N. 20° W., 9 lks. dist., mkd. ¼ S BT on a bark blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 25 S	R 8 W
¼ S	26
¼ S	35
1964	

from which new bearing trees

- A hemlock, 9 ins. diam., bears N. 72½° W., 15 lks. dist., mkd. ¼ S26 BT.
- A hemlock, 10 ins. diam., bears S. 28° E., 45 lks. dist., mkd. ¼ S35 BT.