

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS																									
	<p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. $71\frac{1}{2}^\circ$ E., 53 lks. dist., mkd. T25S R8W S24 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 71° W., 49 lks. dist., mkd. T25S R8W S26 BT.</p> <p style="padding-left: 40px;">A hemlock, 19 ins. diam., bears S. $24\frac{1}{4}^\circ$ E., $5\frac{1}{2}$ lks. dist., mkd. T25S R8W S25 BT.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears N. $51\frac{1}{2}^\circ$ W., 8 lks. dist., mkd. T25S R8W S23 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, madrone, maple, chinqupin, dogwood, live oak, alder, and yew; undergrowth, salal, hazel, Oregon grape, arrowwood, huckleberry, rhododendron, vine maple, poison oak, vines and ferns.</p>																								
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy, of the Twp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, with brass cap mkd. and witnessed as described in the field notes of the 1964 dependent resurvey. of a portion of the W. bdy. of T. 25 S., R. 7 W.</p> <p>S. $84^\circ 06'$ W., bet. secs. 24 and 25.</p> <p>Descend 75 ft. over NW. slope, through heavy timber and light undergrowth.</p>																								
1.90	Ravine, drains N.; asc. 125 ft. over NE. slope.																								
4.70	Spur, slopes N. 15° E.; desc. 165 ft. over NW. slope.																								
7.55	Wet ravine, drains N. 20° E.; sc. 190 ft. over broken NE. slope.																								
13.80	Spur, slopes N. 15° W.; desc. 415 ft. over NW. slope.																								
23.20	Ravine, drains N. 25° W.; asc. 175 ft. over NE. slope.																								
28.10	Spur, slopes NW.; desc. 415 ft. over SW. slope.																								
40.29	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an ironpost, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td>T</td> <td>25</td> <td>S</td> <td>R</td> <td>8</td> <td>W</td> </tr> <tr> <td></td> <td>$\frac{1}{4}$</td> <td>S</td> <td>24</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>S</td> <td>25</td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1965</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. $17\frac{1}{2}^\circ$ W., 24 lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 36° W., 26 lks. dist., mkd. $\frac{1}{4}$ S25 BT.</p> <p>Descend 215 ft. over SW. slope.</p>	T	25	S	R	8	W		$\frac{1}{4}$	S	24					S	25								1965
T	25	S	R	8	W																				
	$\frac{1}{4}$	S	24																						
		S	25																						
					1965																				
46.05	Ravine, drains NW.; asc. 70 ft. over NE. slope.																								
52.05	Spur, slopes N. 30° W.; desc. 240 ft. over NW. slope.																								