

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

A fir, 64 ins. diam., bears N. 60° W., 4 lks.  
dist., no marks remaining on burned bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins.  
in the ground, with brass cap marked.

|        |       |
|--------|-------|
| T 25 S | R 8 W |
| S 14   | S 13  |
| S 23   | S 24  |
| 1964   |       |

from which new bearing trees

A fir, 23 ins. diam., bears N. 14° E., 75 lks.  
dist., mkd. T25S R8W S13 BT.

A cedar, 15 ins. diam., bears S. 43° E., 123 lks.  
dist., mkd. T25S R8W S24 BT.

A fir, 6 ins. diam., bears S. 7¼° W., 57 lks.  
dist., mkd. T25S R8W S23 BT.

A hemlock, 16 ins. diam., bears N. 79½° W., 84 lks.  
dist., mkd. T25S R8W S14 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, madrone, maple, chinquapin,  
dogwood, alder, live oak, myrtle and yew; undergrowth,  
salal, hazel, arrowwood, poison oak, Oregon grape, vine maple,  
huckleberry, vines and ferns.

From the cor. of secs. 13 and 24 only, on the E. bdy. of the  
Twp., monumented with an iron post, 2½ ins. diam., firmly  
set, with brass cap mkd. and witnessed as described in  
the field notes of the 1964 dependent resurvey of a portion  
of the W. bdy. of T. 25 S., R. 7 W.

S. 82° 50' W., bet. secs. 13 and 24.

Ascend 10 ft. over NE. slope, through heavy timber and  
light undergrowth.

1.10 Spur, slopes N. 35° W.; desc. 670 ft. over SW. slope.

28.00 Creek, 1 lk. wide, course N. 65° W.; asc. 400 ft. over  
N.E. slope.

39.78 Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate  
distance; there is no remaining evidence of the original  
corner.

Set an iron post, 28 ins. long 2½ ins. diam., 22 ins.  
in the ground, with brass cap mkd.

|        |       |
|--------|-------|
| T 25 S | R 8 W |
| ¼ S 13 |       |
| S 24   |       |
| 1964   |       |

from which

A fir, 22 ins. diam., bears N. 14½° E., 51 lks.  
dist., mkd. ¼ S13 BT.