

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

A fir, 53 ins. diam., bears S. 20° E., 85 lks. dist.,
mkd. T25S R8W S12 BT on a bark blaze.

(Record, S. 48° E.)

A fir, 45 ins. diam., bears S. 60° W.; 85 lks.
dist., mkd. T25S R8W on decaying bark blaze.

(Record, S. 40° W.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 25 S	R 8 W
S 2	S 1
S 11	S 12
1964	

from which new bearing trees

A fir, 22 ins. diam., bears N. 42° E., 63 lks.
dist., mkd. T25S R8W S1 BT.

A fir, 22 ins. diam., bears S. 71° E., 7 lks.
dist., mkd. T25S R8W S12 BT.

A fir, 8 ins. diam., bears S. 57½° W., 44 lks.
dist., mkd. T25S R8W S11 BT.

A fir, 15 ins. diam., bears N. 61° W., 50 lks.
dist., mkd. T25S R8W S2 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, yew, maple, madrone, alder,
chinquapin, dogwood, live oak and myrtle; undergrowth,
salal, poison oak, Oregon grape, hazel, arrowwood,
huckleberry, vine maple, ferns and vines.

From the true point for the cor. of secs. 1, 6, 7 and 12,
on the E. bdy. of the Twp., which point is S. 0° 13' E.,
1.35 chs. dist. from the witness cor. for the cor. of
secs. 1, 6, 7 and 12, monumented with an iron post, 2½ ins.
diam., firmly set, with brass cap mkd. and witnessed as
described in the field notes of the 1964 dependent resurvey
of a portion of the W. bdy. of T. 25 S., R. 7 W.

N. 82° 27' W., bet. secs. 1 and 12.

Ascend 550 ft. over S.E. slope, through heavy timber and
dense undergrowth.

18.55 Ridge, bears N. 20° E. and S. 20° W.; desc. 5 ft. over
N.W. slope.

19.87 Point for the E 1/16 sec. cor. of secs. 1 and 12.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.
in the ground, to bedrock, and in a mound of stone, 3 ft.
base, to top, with brass cap mkd.

E 1/16	S 1
	S 12
1965	

from which