

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 25 S	R 8 W
¼ S	23
¼ S	26
1965	

from which

A fir, 10 ins. diam., bears N. 42½° E., 62 lks. dist., mkd. ¼ S23 BT.

A fir, 6 ins. diam., bears S. 75½° W., 40 lks. dist., mkd. ¼ S26 BT.

Descend 225 ft. over S. W. slope.

47.95 Creek, 4 lks. wide, course N. 15° W.; asc. 150 ft. over N.E. slope.

51.15 Spur, slopes N.; desc. 170 ft. over N. W. slope.

56.35 Cougar Creek, 10 lks. wide, course N. 20° E.; asc. 120 ft. over S.E. slope.

73.55 Top of ascent, slopes S. E.; desc. 10 ft. over S.W. slope.

74.60 Creek, 1 lk. wide, course S. 75° E; asc. 195 ft. over N. E. slope.

80.98 The cor. of secs. 22, 23, 26 and 27, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, monumented with an iron pipe, 1 in. diam., firmly set, protruding 6 ins. above ground, from which the remaining original bearing trees:

A fir, 38 ins. diam., bears N. 73° E.; 25 lks. dist., with scribe marks T 2 visible on a bark blaze. This tree was remarked by Godfrey alongside the original blaze. This blaze is now partially healed. (Record bearing, N. 53° E.)

A fir snag, 34 ins. diam., bears S. 18½° E., 26 lks. dist., with partial scribe marks visible on a bark blaze. (Record bearing, S. 33° E.)

and bearing trees marked by Godfrey

A hemlock, 5 ins. diam., bears S. 44 ¾° E., 52 lks. dist., mkd. 26 CS BT on a double blaze.

A hemlock, 8 ins. diam., bears S. 66 ¾° W., 57 lks. dist., mkd. T25S R8W S27 CS BT on a double blaze.

A hemlock, 8 ins. diam., bears N. 56° W., 6 lks. dist., mkd. T25S R8W S22 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 25 S	R 8 W
S 22	S 23
S 27	S 26
1965	

from which a new bearing tree

A fir, 37 ins. diam., bears N. 24 ¾° E., 68 lks. dist., mkd. T25S R8W S23 BT.