

County Surveyor's Record, Douglas County, Oregon

12773

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS	Land, mountainous. Soil, rocky clay, Timber, fir, cedar, hemlock, maple, madrone, chinquapin, alder, dogwood, live oak, myrtle and yew; undergrowth, salal, arrowwood, hazel, vine maple, huckleberry, Oregon grape; rhododendron, poison oak, vines and ferns.
	N. 0° 47' W., bet. secs. 22 and 23. Descend 145 ft. over N.E. slope through heavy timber and dense undergrowth.
3.20	Creek, 3 lks. wide, course S. 60° E.; asc. 385 ft. over S.W. slope.
18.50	Dirt road, 25 lks. wide, bears N. 70° E. and S. 70° W.
19.45	Spur, slopes S. 65° E.; desc. 90 ft. over N.E. slope.
21.15	Dirt road, 25 lks. wide, bears N. 55° W. and S. 30° E., in a curve.
28.75	Bottom of descent, slopes E.; asc. 110 ft. over S.E. slope.
36.20	Spur ridge, bears N.E. and S.W.; desc. 70 ft. over N.W. slope.
39.54	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, determined at record bearing from the remains of the original bearing trees: A fir, 30 ins. diam., bears N. 67° E., 12 lks. dist., 10 lks. to face, mkd. $\frac{1}{4}$ S on a bark blaze. (Record, 10 lks.) A fir snag, 18 ins. diam., bears S. 80° W., 17 lks. dist., 15 lks. to face, no marks visible on opened blaze. (Record, 15 lks.) at the corner point Set an iron post, 28 ins. long 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd. FO. OK 6/94 BY QUIMBY M 120-17 T 25 S R 8 W $\frac{1}{4}$ S 22/S 23 1965 from which new bearing trees A fir, 15 ins. diam., bears N. 38° E., 24 lks. dist., mkd. $\frac{1}{4}$ S23 BT. A fir, 12 ins. diam., bears N. 15 $\frac{1}{2}$ ° W., 48 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S22 BT.
	N. 0° 51' W., beginning new measurement. Descend 100 ft. over gently sloping N.W. slope.
28.90	Edge of wide ridge top, bears N. 70° E. and S. 70° W.; desc. 375 ft. over N.W. slope.
40.61	The cor. of secs. 14, 15, 22 and 23, determined at record bearing and distance from the original N.W. bearing tree: