

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 8 W.

CHAINS

A maple, 48 ins. diam., bears N. 63° W., 30 lks.
dist., with old axe marks on the bark.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins.
in the ground, with brass cap mkd.

T 25 S R 8 W	
S 15	S 14
S 22	S 23
1965	

from which new bearing trees

A hemlock, 17 ins. diam., bears N. 12° E., 27½ lks.
dist., mkd. T25S R8W S14 BT.

A fir, 30 ins. diam., bears S. 86½° E., 62 lks.
dist., mkd. T25S R8W S23 BT.

A maple, 21 ins. diam., bears S. 56¼° W., 74 lks.
dist., mkd. T25S R8W S22 BT.

A fir, 29 ins. diam., bears N. 40° W., 99½ lks.
dist., mkd. T25S R8W S15 BT.

Land, mountainous

Soil, rocky clay.

Timber, fir, cedar, hemlock, maple, madrone, chinquapin,
alder, and dogwood; undergrowth, salal, rhododendron,
arrowwood, Oregon grape, huckleberry, vine maple, poison
oak, vines and ferns.

From the cor. of secs. 13, 14, 23 and 24.

N. 89° 18' W., bet. secs. 14 and 23.

Descend 360 ft. over sW. slope, through heavy timber and
dense undergrowth.

9.30 Cougar Creek, 15 lks. wide, course N. 20° W.; asc. 705 ft.
over N.E. slope.

28.35 Spur, slopes N.; desc. 255 ft. over N.W. slope.

37.05 Creek, 1 lk. wide, course N.; asc. 120 ft. over N.E.
slope.

41.45 Spur, slopes N.; desc. 5 ft. over N.W. slope.

41.64 Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate
distance; there is no remaining evidence of the original
corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 25 S R 8 W	
¼	S 14
¼	S 23
1965	

from which

A fir, 14 ins. diam., bears N. 56° E., 19½ lks.
dist., mkd. ¼ S14 BT.