

# County Surveyor's Record, Douglas County, Oregon

12784

Dependent Resurvey, Portion of the S. Bdy., T. 28 S., R. 4 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T 28 S	
R 4 W	R 3 W
S 36	S 31
S 6	
T 29 S	R 3 W
1964	

from which new bearing trees

A fir, 42 ins. diam., bears N. 48° E., 85 lks. dist., mkd. T28S R3W S31 BT.

A fir, 16 ins. diam., bears N. 50 ¾° W., 67 lks. dist., mkd. T28S R4W S36 BT.

N. 89° 24' W., on the S. bdy. of sec. 36, marking and blazing the true line.

Descend 390 ft. over W. slope, changing to broken N.W. slope, through heavy timber and light undergrowth.

27.94 True point for the closing corner of Tps. 29 S., Rs. 3 and 4 W., hereinafter described.

Descend 30 ft. over N.W. slope.

29.65 Ravine, drains N. 20° W.; asc. 80 ft. over N.E. slope.

36.90 Spur, slopes N. 20° W.; desc. 75 ft. over N.W. slope.

39.58 Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 4 W	
¼	S 36
S	1
T 29 S	
1964	

from which

A cedar, 13 ins. diam., bears N. 46½° W., 11 lks. dist., mkd. ¼ S36 BT.

A fir, 12 ins. diam., bears S. 18½° E., 71 lks. dist., mkd. ¼ S 1 BT.

Descend 560 ft. over N.W. slope.

42.00 Enter logged area, edge bears N. and S.

50.65 S.E. cor. of timber, edges bear N. and W.

57.65 Enter timber, edges bear E. and S.

73.30 Enter logged area, edge bears N. and S.

75.20 Dirt road, 20 lks. wide, bears N. 20° E., and S. 20° W.

79.16 The cor. of secs. 1, 2, 35 and 36, remonumented and recorded by James W. Byron, Deputy County Surveyor, in 1958, with an iron post, 1 in. diam., 14 ins. above ground, firmly set, with brass cap mkd.