

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of the S. Bdy., T. 28 S., R. 4 W.

CHAINS

COUNTY SURVEYORS OFFICE

T 28 S	R
S 35 S 36	4
S 2 S 1	W
T 29 S	
1958	

from which the remaining original bearing trees

A fir snag, 23 ins. diam., bears sS.53° W., 18 lks. dist., mkd. S2 and other illegible scribe marks on opened blaze. (Record, S. 40° W.)

A fir snag, 16 ins. diam., bears N. 44½° W., 30 lks. dist., mkd. S35 T28 and other illegible scribe marks on opened blaze. (Record, N. 46° W., 28 lks.)

and bearing trees mkd. by Byron

A sawed cedar stump, 17 ins. diam., bears N. 61½° E., 11 lks. dist., mkd. S36 T28S R4W CS BT on double blaze.

A cedar, 11 ins. diam., bears S. 2° E., 26 lks. dist., mkd. S 1 T29S R4W CS BT on double blaze.

A fir, 16 ins. diam., bears S. 80° W., 48 lks. dist., mkd. S2 T29S R4W CS BT on double blaze.

A fir, 35 ins. diam., bears N. 3½° W., 23 lks. dist., mkd. with a partially healed double blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 61½° E., 98 lks. dist., mkd. T28S R4W S36 BT.

Add the marks BLM to the brass cap.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, yew madrone, maple, alder, dogwood, pine and chinquapin; undergrowth, salal, hazel, rhododendron, poison oak, Oregon grape, arrowwood, vine maple, ferns and vines.

Dependent Resurvey of the W. Bdy., T.29 S., R. 3 W.,
Willamette Meridian, Oregon

(Restoring the 1855 survey by Nathaniel Ford, the 1858 retracement by Dennis Hathorn, and the 1881 retracement by William H. Byars)

The cor. of Tps. 29 and 30 S., Rs. 3 and 4 W., perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1928, from the remains of the original bearing trees, which are no longer in existence; subsequently remonumented by James W. Byron, Deputy County Surveyor, in 1962, with an iron post, 1 in. diam., 18 ins. above ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

R	T 29 S	R
4	S 36 S 31	3
W	S 1 S 6	W
	T 30 S	
	1962	