

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the W. Bdy., T. 29 S., R. 3 W.

CHAINS

COUNTY SURVEYORS OFFICE

	T 29 S		
R	S 25		R
4	S 36		3
W	1962		W

from which the Evans bearing tree

A sawed fir stump, 18 ins. diam., bears S. 26° W., 42 lks. dist., mkd. BT on detached bark.

and bearing tree marked by Byron

A Cedar, 18 ins. diam., bears S. 21¼° W., 200 lks. d dist., mkd. T29S R4W S36 CS BT on double blaze.

A cedar, 20 ins. diam., bears N. 85° W., 133 lks. dist., mkd. T29S R4W S25 CS BT on double blaze.

Add the marks ELM to the brass cap.

N. 0° 42' E., beginning new measurement.

Descend 5 ft. over N.W. slope, through logged area.

1.30 Ravine, drains S. 70° W.; asc. 200 ft. over S. slope.

2.05 Dirt road, 15 lks. wide, bears N. 65° E. and S. 56° W.

2.20 Enter along W. edge of logged area, edge bears N. and S. 65° W.

10.70 Spur, slopes W.; desc. 45 ft. over N.W. slope.

14.30 Ravine, drains S. 70° W.; asc. 30 ft. over S.W. slope.

18.75 Top of ascent, slopes W.; desc. 50 ft. over N.W. slope.

23.10 Ravine, drains S. 50° W.; asc. 120 ft. over S.E. slope.

27.00 Enter heavytimber and light undergrowth, edge bears S. and E.

27.56 Point for the ¼ sec. cor. of sec. 30 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

	T 29 S	
	¼	
	S 30	
	R 3 W	
1964		

from which

A fir, 10 ins. diam., bears N. 41½° E., 29½ lks. dist., mkd. ¼ S30 BT.

A cedar, 13 ins. diam., bears S. 85½° E. 13 lks. dist., mkd. ¼ S30 BT.

Ascend 5 ft. over S.E. slope.