

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the W. Bdy., T. 29 S., R. 3 W.

<p>CHAINS</p> <p>27.75</p> <p>32.25</p> <p>38.365</p> <p>39.70</p> <p>47.725</p> <p>51.20</p> <p>54.95</p> <p>58.25</p> <p>60.45</p>	<p>Spur, slopes S. 60° W.; desc. 30 ft. over N.W. slope.</p> <p>Bottom of descent, slopes W.; asc. 45 ft. over S.W. slope.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 25 only, on the E. bdy. of T. 29 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 29 S</td> <td> </td> </tr> <tr> <td></td> <td>$\frac{1}{4}$</td> </tr> <tr> <td>S 25</td> <td> </td> </tr> <tr> <td>R 4 W</td> <td> </td> </tr> <tr> <td>1964</td> <td></td> </tr> </table> </div> <p>from which</p> <p>A fir, 12 ins. diam., bears S. $19\frac{1}{2}$° W., 22 lks. dist., mkd. T29S R4W E$\frac{1}{4}$ S25 CS BT, by Deputy County Surveyor, A. R. Evans, in 1949.</p> <p>A fir, 15 ins. diam., bears N. $42\frac{3}{4}$° W., 24 lks. dist., mkd. $\frac{1}{4}$ S25 BT.</p> <p>From this point a point established by A. R. Evans, Deputy County Surveyor, in 1949, monumented with an iron pipe, 1 in. diam., 6 ins. above ground, firmly set, bears S. 8° 30' E., 0.26 chs. dist., from which bearing trees marked by Evans.</p> <p>A madrone, 19 ins. diam., bears S. 28° W., 65 lks. dist., mkd. T29S R4W E$\frac{1}{4}$ S25 CS BT.</p> <p>A fir, 12 ins. diam., bears N. 64° W., 13 lks. dist., mkd. T29S R4W E$\frac{1}{4}$ S25 CS BT.</p> <p>Ascend 10 ft. over S.W. slope.</p> <p>Ridge and trail, bears N.W. and S.E.; desc. 130 ft. over N.E. slope.</p> <p>Point for the N $\frac{1}{16}$ sec. cor. of sec. 30, only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>N 1/16</td> <td> </td> </tr> <tr> <td>S 30</td> <td> </td> </tr> <tr> <td>1964</td> <td></td> </tr> </table> </div> <p>from which</p> <p>A cedar, 7 ins. diam., bears N. $73\frac{1}{2}$° E., $8\frac{1}{2}$ lks. dist., mkd. N 1/16 S30 BT.</p> <p>A fir, 20 ins. diam., bears S. $13\frac{3}{4}$° E., 43 lks. dist., mkd. N 1/16 S30 BT.</p> <p>Descend 85 ft. over N.E. slope.</p> <p>Ravine, drains E.; asc. 20 ft. over S.E. slope.</p> <p>Spur, slopes N.E.; desc. 60 ft. over N.E. slope.</p> <p>Ravine, drains N. 75° E.; asc. 15 ft. over S.E. slope.</p> <p>Spur, slopes N. 35° E.; desc. 210 ft. over N.W. slope.</p>	T 29 S			$\frac{1}{4}$	S 25		R 4 W		1964		N 1/16		S 30		1964	
T 29 S																	
	$\frac{1}{4}$																
S 25																	
R 4 W																	
1964																	
N 1/16																	
S 30																	
1964																	

*FD. OK 7/19
SEC M 10-95*