

Dependant Resurvey of the W. Bdy., T. 29 S., R. 3 W.

CHAINS

N. 1° 30' E., beginning new measurement.

Ascend 100 ft. over broken S.E. slope.

13.89

Point for the closing cor. of secs. 12 and 13, on the E. bdy. of T. 29 S., R. 4 W., at proportionate distance in latitude; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins in the ground, with brass cap mkd.

	T 29 S		T 29 S
CC	S 12		S 18
	S 13		
	R 4 W		R 3 W
	1964		

from which

A fir, 38 ins. diam., bears S. 54¼° W., 72 lks. dist., mkd. T29S R4W S13 CC BT.

A fir, 6 ins. diam., bears N. 62½° W., 71 lks. dist., mkd. T29S R4W S12 CC BT.

Ascend 40 ft. over S.E. slope, through logged area.

15.55

Spur, slopes S. 60° E.; asc. 85 ft. over S.E. slope.

20.00

Ravine, drains S. 60° E.; asc. 85 ft. over s S.E. slope. changing to S. slope.

29.35

Top of ascent, slopes E.; desc. 105 ft. over N.E. slope.

34.08

Short Wiley Creek, 1 lk. wide, course S.E.; asc. 105 ft. over S.W. slope, changing to S.E. slope.

38.60

The cor. of secs. 7 and 18 only, determined from the remains of the original bearing trees:

A yew snag, 13 ins. diam., bears N. 47° E., 27 lks. dist., no marks remaining.

A stump hole, bears S. 25° E., 20 lks. dist.

A stump hole, bears S. 20° W., 15 lks. dist.

A yew, 14 ins. diam., bears N. 25° W., 9 lks. dist., no marks remaining on opened blaze. (Byars record dist., 19 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

	T 29 S		T 29 S
	S 12		S 7
			S 18
	R 4 W		R 3 W
	1964		

from which new bearing trees

A fir, 12 ins. diam., bears N. 34¼° E., 40 lks. dist., mkd. T29S R3W S7 BT.

A fir, 7 ins. diam., bears S. 61¼° E., 35 lks. dist., mkd. T29S R3W S18 BT.