

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the W. Bdy., T. 29 S., R. 3 W.

CHAINS	Land, mountainous. Soil, rocky clay. Timber, fir, cedar, hemlock, pine, maple, madrone, yew, alder, dogwood, oak and chinquapin; undergrowth, salal, poison oak, hazel, Oregon grape, arrowwood, vine maple, blackberry, young timber, vines and ferns.										
14.90	<p>N. 2° 05' E., on the W. bdy. of sec. 7.</p> <p>Ascend 115 ft. over S.E. slope, along E. edge of logged area, through light undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 12 only, on the E. bdy. of T. 29 S., R. 4 W., at midpoint in latitude.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 29 S</td><td> </td></tr> <tr><td>$\frac{1}{4}$</td><td> </td></tr> <tr><td>S 12</td><td> </td></tr> <tr><td>R 4 W</td><td> </td></tr> <tr><td>1964</td><td></td></tr> </table> </div>	T 29 S		$\frac{1}{4}$		S 12		R 4 W		1964	
T 29 S											
$\frac{1}{4}$											
S 12											
R 4 W											
1964											
35.30	<p>from which</p> <p>A cedar, 24 ins. diam., bears S. $33\frac{1}{2}^{\circ}$ W., 98 lks. dist., mkd. $\frac{1}{4}$ S12 BT.</p> <p>A hemlock, 18 ins. diam., bears N. $77\frac{1}{2}^{\circ}$ W., 78 lks. dist., mkd. $\frac{1}{4}$ S12 BT.</p> <p>Ascend 380 ft. over S.E. slope, changing to S.W. slope.</p> <p>Spur, slopes S. 55° E.; desc. 50 ft. over N.E. slope.</p>										
38.83	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 7 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T 29 S</td><td> </td></tr> <tr><td>$\frac{1}{4}$</td><td> </td></tr> <tr><td>S 7</td><td> </td></tr> <tr><td>R 3 W</td><td> </td></tr> <tr><td>1964</td><td></td></tr> </table> </div>	T 29 S		$\frac{1}{4}$		S 7		R 3 W		1964	
T 29 S											
$\frac{1}{4}$											
S 7											
R 3 W											
1964											
40.60	<p>from which</p> <p>A cedar, 17 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ E., 85 lks. dist., mkd. $\frac{1}{4}$ S7 BT.</p> <p>A fir, 7 ins. diam., bears S. 36° E., 54 lks. dist., mkd. $\frac{1}{4}$ S7 BT.</p> <p>Descend 40 ft. over N.E. slope.</p> <p>Ravine, drains S. 70° E.; asc. 105 ft. over S.E. slope.</p>										
47.35	Spur, slopes S. 55° E.; desc. 20 ft. over N.E. slope.										
52.35	Ravine, drains E.; asc. 15 ft. over S.E. slope.										
54.51	Point for the closing cor. of secs. 1 and 12, on the E. bdy. of T. 29 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.										