

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the W. Bdy., T. 29 S., R. 3 W.

CHAINS

A fir, 42 ins. diam., bears S. 32° E., 61 lks.  
dist., mkd. with illegible scribe marks.  
(Record, S. 30° E.)

A down fir, 32 ins. diam., bears S. 35° W., 34 lks.  
dist., mkd. with a healed blaze.

and bearing trees mkd. by Byron

A cedar, 17 ins. diam., bears S. 30° E., 43 lks.  
dist., mkd. S6 T29S R3W CS BT on double blaze.

A cedar, 25 ins. diam., bears S. 72¼° W., 82 lks.  
dist., mkd. S1 T29S R4W CS BT on double blaze.

Add the marks BLM and AM to the brass cap.

28.74

Intersect the S. bdy. of T. 28 S., R. 4 W.

Point for the closing corner of Tps. 29 S., Rs. 3 and 4 W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

```

T 28 S R 4 W
  S 36
  S 1 | S 6
R 4 W | R 3 W
  T 29 S
    CC
    1964
    
```

from which the bearing tree mkd. by Byron in 1958:

A cedar, 17 ins. diam., bears S. 25° E., 54 lks.  
dist., mkd. S6 T29S R3W CS BT on double blaze.

and a new bearing tree:

A yew, 8 ins. diam., bears S. 68° W., 18 lks. dist.,  
mkd. T29S R4W S1 CC BT.

From this point the ¼ sec. cor. of secs. 1 and 36, on the  
S. Bdy. of T. 28 S., R. 4 W., bears N. 89° 24' W., 11.64 chs.  
dist., heretofore described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, madrone, hemlock, yew, alder,  
maple, dogwood, live oak and chinquapin: undergrowth,  
salal, poison oak, Oregon grape, hazel, arrowwood, young  
timber, ferns and vines.

Dependent Resurvey of a Portion of the N. Boundary,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the 1881 survey by William H. Byars and the  
1910 retracement by William N. Gibb)

The corner of secs. 2 and 3 only, on the N. bdy. of T. 29 S.,  
R. 3 W., remonumented and recorded by James W. Byron, Deputy  
County Surveyor, in 1962, with an iron post, 1 in. diam.,  
12 ins. above ground, firmly set, with brass cap mkd.

COUNTY SURVEYOR OFFICE  
T 28 S R 3 W

```

S 3 | S 2
  T 29 S
    1962
    
```