

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 29 S., R. 4 W.

CHAINS

from which the original bearing trees:

A cedar snag, 50 ins. diam., bears N. 50° E., 70 lks. dist., mkd. T28S R3W BT on an open blaze.

A madrone, 23 ins. diam., bears S. 15° E., 42½ lks. dist., no marks visible on rotted blaze. (Record, 38 lks.)

A cedar, 28 ins. diam., bears S. 64° W., 35 lks. dist., mkd. 29 R on original open blaze, remarked T29S R3W on open blaze alongside, and S3 T29S R3W CS BT on double blaze. (Record, S. 60° W.)

A fir, 38 ins. diam., bears N. 54° W., 60 lks. dist., mkd. S T28S R3W B on bark blaze. (Record, N. 62° W.)

and a bearing tree mkd. by Byron

A fir, 12 ins. diam., bears S. 30° E., 37 lks. dist., with a partially healed double blaze.

Add the marks BLM to the brass cap.

N. 89° 30' W., on the N. Bdy. of sec. 3, marking and blazing the true line.

Descend 125 ft. over S.W. slope, through heavy timber and light undergrowth.

8.35 Creek, 2 lks. wide, course S.; asc. 435 ft. over E. slope, changing to S.E. slope.

25.60 Spur, slopes S. 25° E.; desc. 15 ft. over S.W. slope.

29.15 Ravine, drains S.; asc. 115 ft. over S.E. slope.

33.85 Spur, slopes S.; desc. 60 ft. over S.W. slope.

38.88 Ravine, drains S. 15° E.; asc. 25 ft. over S.E. slope.

39.90 The ¼ sec. cor. of sec. 3 only, determined at record bearing and distance from the remains of the bearing tree mkd. by Gibb in 1910:

A down madrone, 7 ins. diam., bears S. 70° W., 20 lks. dist., mkd. ¼ S3 BT on an open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 3 W

$$\frac{1}{4} S 3$$
 T 29 S R 3 W
 1964

from which new bearing trees

A fir, 8 ins. diam., bears S. 41½° E., 41 lks. dist., mkd. ¼ S 3 BT.