

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 29 S., R. 3 W.

CHAINS

A cedar, 8 ins. diam., bears S. $47\frac{1}{2}^\circ$ W., 48 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S 3 BT.

S. $88^\circ 59'$ W., beginning new measurement.

Ascend 70 ft. over S.E. Slope, through heavy timber and light undergrowth.

4.385 The closing corner of secs. 33 and 34, on the S. bdy. of T. 28 S., R. 3 W., remonumented and recorded by James W. Byron, Deputy County Surveyor, in 1962, with an iron post, 1 in. diam., 14 ins. above ground, firmly set, with the original, unmarked, granite stone, 6 x 9 x 9 ins., lying alongside, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 28 S	
CC	
S 33	S 34

T 29 S
1962

from which the original bearing trees

A madrone, 13 ins. diam., bears N. 21° E., 53 lks. dist., with scribe marks visible on an open blaze. (Record, 52 lks.)

A madrone, 10 ins. diam., bears N. 36° W., 27 lks. dist., no marks visible on an open blaze. (Record, 26 lks.)

Ascend 10 ft. over s S.E. Slope.

5.95 Spur, slopes S. 40° W.; desc. 545 ft. over N.W. slope.

13.30 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.

30.20 Creek, 1 lk. wide, course S. 10° W.; asc. 70 ft. over S.E. slope.

37.88 The cor. of secs. 3 and 4 only, perpetuated and recorded by Warren D. Hootman, Registered Land Surveyor, in 1960, with an iron pipe, 1 in. diam., 8 ins. above ground, from which the S.E. bearing tree mkd. by Gibb in 1910:

A fir, 15 ins. diam., bears S. 40° E., 53 lks. dist., mkd. 29S R3W S3 BT on an opened blaze.

and a bearing tree mkd. by Hootman

A madrone, 13 ins. diam., bears N. 5° W., 18 lks. dist., mkd. T28S R3W S33 BT on an open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 28 S R 3 W	
S 33	
S 4	S 3
T 29 S	R 3 W

1964