

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Bdy., T. 29 S., R. 3 W.

## CHAINS

from which a new bearing tree:

A fir, 7 ins. diam., bears S.  $17^{\circ}$  W., 85 lks. dist.,  
mkd. T29S R3W S4 BT.

Reset iron pipe alongside iron post.

From this point, a point established by Claude Kerr,  
Registered Logging Engineer, in 1950, bears S.  $53\frac{1}{2}^{\circ}$  E.,  
0.25 chs. dist., monumented with a cedar post, 3 ins. square,  
36 ins. above ground, firmly set, mkd. S3 on S.E., and S4  
on S.W. side, from which trees mkd. by Kerr:

A cedar, 23 ins. diam., bears S.  $45^{\circ}$  E., 36 lks.  
dist., mkd. T29S R3W S3 BT on an open blaze.

A fir, 23 ins. diam., bears S.  $56^{\circ}$  W.,  $37\frac{1}{2}$  lks.  
dist., mkd. with a healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, pine, fir, cedar, hemlock, madrone, maple, chinquapin,  
yew, alder, dogwood and live oak: undergrowth, poison oak,  
salal, huckleberry, Oregon grape, hazel, arrowwood, vine  
maple, ferns and vines.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 29 S., R. 3 W., Willamette Meridian, Oregon.

(Restoring the 1881 survey by William H. Byars)

The cor. of secs. 11 and 14 only, on the E. bdy. of sec. 15,  
perpetuated and recorded by James W. Byron, Deputy County  
Surveyor, in 1957, with an iron rod,  $\frac{3}{4}$  in. diam., 10 ins.  
above ground, firmly set, from which the remains of the  
original bearing trees:

A down fir, 23 ins. diam., bears N.  $55^{\circ}$  E., 31 lks.  
dist., mkd. S11 BT and remarked T29S R3W S11 CS BT  
on bark blaze.

A fir snag, 24 ins. diam., bears S.  $35^{\circ}$  E., 25 lks.  
dist., 24 lks. to face, mkd. S14 T29S R3W T on  
bark blaze. (Record, 24 lks.)

and bearing trees mkd. by Byron in 1957

A cedar stump, 17 ins. diam., bears N.  $12\frac{1}{2}^{\circ}$  W., 39 lks.  
dist., mkd. T29S R3W S15 CS BT on double blaze.

A cedar, 13 ins. diam., bears S.  $25\frac{1}{4}^{\circ}$  E., 35 lks.  
dist., mkd. T29S R3W S14 CS BT on double blaze.

and a bearing tree not of record

A fir, 16 ins. diam., bears N.  $1\frac{1}{2}^{\circ}$  E., 21 lks.  
dist., mkd. T29S R3W S11 CS BT on double blaze.

AT the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.