

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 3 W.

CHAINS

T 29 S R 3 W  
 $\frac{1}{4}$   
 S 10 | S 11  
 1964

from which new bearing trees:

A fir, 12 ins. diam., bears N. 67° E., 35 lks.  
 dist., mkd.  $\frac{1}{4}$  S11 BT.

A fir, 7 ins. diam., bears N. 84 $\frac{1}{2}$ ° W., 123 lks.  
 dist., mkd.  $\frac{1}{4}$  S10 BT.

Corner falls in old rail fence which bears N. and S.

N. 2° 44' W., beginning new measurement.

Descend 15 ft. over nearly level bottom land, through dense undergrowth.

2.30 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.

7.20 South Myrtle Creek, 15 lks. wide, course S. 45° W., from N.; continue up creek.

16.00 Leave South Myrtle Creek, course S., from N.E.; asc. 145 ft. over S.E. slope.

17.10 Gravel road, 30 lks. wide, bears N. 20° E. and S.W.

31.40 Top of ascent, slopes E.; desc. 15 ft. over N.E. slope.

33.30 Dirt road, 20 lks. wide, bears N. 55° E. and S. 55° W.

33.75 Ravine, drains S.E.; asc. 75 ft. over S.W. slope, changing to S. E. slope.

39.57 Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

FO. & B.  
 RUPPERT 5/92  
 1992. 0038

T 29 S R 3 W  
 $\frac{1}{4}$   
 S 3 | S 2  
 S 10 | S 11  
 1964

from which

A fir, 10 ins. diam., bears N. 28 $\frac{1}{2}$ ° E., 168 lks.  
 dist., mkd. T29S R3W S2 BT.

A fir, 10 ins. diam., bears S. 40° E., 46 lks.  
 dist., mkd. T29S R3W S11 BT.

A fir, 7 ins. diam., bears S. 51 $\frac{1}{4}$ ° W., 8 lks.  
 dist., mkd. T29S R3W S10 BT.

A fir, 10 ins. diam., bears N. 47 3/4° W., 103 lks.  
 dist., mkd. T29S R3W S3 BT.

Land, mountainous.  
 Soil, rocky clay.  
 Timber, fir, pine, cedar, madrone, maple, yew, chinqupin, alder, dogwood, hemlock and live oak; undergrowth; salal, Oregon grape, poison oak, hazel, arrowwood, vine maple, huckleberry, vines and ferns.