

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 3 W.

CHAINS

From the cor. of secs. 1, 2, 11 and 12, remonumented and recorded by James W. Byron, Deputy County Surveyor, in 1962, with an iron post, 1 in. diam., 6 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYOR OFFICE

	T 29 S	R
S 2	S 1	3
S 11	S 12	W
1962		

from which the remaining original bearing trees

A fir, 54 ins. diam., bears N. 85° E., 46 lks. dist., no original marks remaining. Remarkd T29S R3W S1 CS BT on bark blaze by Byron. (Record, N. 80° E.)

A sawed fir stump, 36 ins. diam., bears N. 50° W., 45 lks. dist., 43 lks. to face, with scribe mark 2 on an opened blaze. (Record, 43 lks.)

and bearing trees mkd. by Byron

A fir, 13 ins. diam., bears S. 32½° E., 29½ lks. dist., with a partially healed double blaze.

A fir, 11 ins. diam., bears S. 86° W., 46 lks. dist., with a partially healed double blaze.

A fir, 21 ins. diam., bears N. 12° W., 25 lks. dist., with a partially healed double blaze.

Add the marks BLM to the brass cap.

N. 86° 34' W., bet. secs. 2 and 11.

Descend 160 ft. over S.W. slope, through light timber and scattering undergrowth.

10.65 Ravine, drains S.; asc. 95 ft. over S.E. slope.

15.25 Spur, slopes S. 60° W.; desc. 360 ft. over N.W. slope.

38.74 Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

	T 29 S R 3 W
¼	S 2
	S 11
1964	

from whic

A fir, 6 ins. diam., bears N. 19° E., 55 lks. dist., mkd. ¼ S2 BT.

A fir, 17 ins. diam., bears S. 48½° E., 36 lks. dist., mkd. ¼ S11 BT.

Descend 270 ft. over N.W. slope, changing to S.W. slope.

47.75 Creek, 1 lk. wide, course N. W.; asc. 50 ft. over N.W. slope.