

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 29 S., R. 3 W.

## CHAINS

18.81

Point for the W 1/16 sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{W } 1/16 \quad \frac{\text{S } 3}{\text{S } 10} \\ 1964 \end{array}$$

from which

A cedar, 32 ins. diam., bears N. 14° W., 19 lks. dist., mkd. W 1/16 S3 BT.

A cedar, 8 ins. diam., bears S. 29° W., 79 lks. dist., mkd. W 1/16 S10 BT.

Descend 60 ft. over SW. slope, along N. side of logged area

25.65

Ravine, drains S.; asc. 35 ft. over SE. slope.

27.75

Spur, slopes S. 15° W.; desc. 75 ft. over SW. slope.

33.15

Lally Creek, 3 lks. wide, course S.; asc. 110 ft. over E. slope.

37.62

The cor. of secs. 3, 4, 9 and 10, reestablished and recorded by Claude Kerr, Logging Engineer, in 1950 at the intersection of old blazed lines. Subsequently remonumented by James W. Byron, Deputy County Surveyor, in 1962, with an iron post, 1 in. diam., 14 ins. above ground, firmly set, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

$$\begin{array}{r} \text{T } 29 \text{ S} \\ \text{S } 4 \text{ | } \text{S } 3 \\ \hline \text{S } 9 \text{ | } \text{S } 10 \\ 1962 \end{array} \begin{array}{l} \text{R} \\ 3 \\ \text{W} \end{array}$$

from which a bearing tree mkd. by Kerr

A fir, 23 ins. diam., bears N. 6° W., 46 lks. dist., with a partially healed blaze.

and bearing trees mkd. by Byron

A fir, 8 ins. diam., bears S. 11° E., 29 lks. dist., with a partially healed double blaze.

A fir, 8 ins. diam., bears S. 16½° W., 14 lks. dist., with a partially healed double blaze.

and a new bearing tree

A fir, 8 ins. diam., bears N. 89 ¾° E., 71 lks. dist., mkd. T29S R3W S3 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, hemlock, madrone, maple, yew, chinquapin, alder, dogwood, and live oak; undergrowth, salal, poison oak, huckleberry, Oregon grape, hazel, vine maple, arrowwood, blackberry, ferns and vines.

N. 0° 02' W., bet. secs. 3 and 4.

Descend 10 ft. over NE. slope, along E. edge of logged area, through light undergrowth.