

County Surveyor's Record, Douglas County, Oregon

T. 31 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of that portion of township 31 south, range 6 west, Willamette Meridian, Oregon, pertaining to this resurvey, is as follows:

The north boundary was surveyed by Addison R. Flint in 1885, as shown on the official plat of survey approved Dec. 10, 1855. The subdivisional lines were surveyed by William H. Byars in 1882, as shown on the official plat of survey approved October 5, 1882.

The survey was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions, based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding, or crossing, public lands were blazed. All lines not forming closures were chained twice.

The resurvey was executed in accordance with the specifications as set forth in the Manual of Surveying Inst., 1947, and Special Inst. dated June 11, 1965, under Group No. 585.

The directions of the lines were determined by the solar transit method.

The geographic position of the southeast corner of section 5, as scaled from the Canyonville, Oregon quadrangle map, prepared by the U. S. Geological Survey, in 1954, is as follows:

Latitude $42^{\circ} 53.9' N.$ Longitude $123^{\circ} 25.5' W.$

The mean magnetic declination is $19^{\circ} 15' E.$

Dependent Resurvey of a Portion of the N. Bdy.,
T. 31 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Addison R. Flint.)

From the cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., perpetuated and recorded by Ben B. Irving, County Surveyor, in 1954, monumented with an iron post, 1 in. diam., firmly set, extending 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS

T 30 S R 6 W

32 | 33

5 | 4

T 31 S R 6 W

1954

OFFICE

from which the remaining original bearing trees:

A fir, 26 ins. diam., bears S. $60^{\circ} W.$, 32 lks. dist., with fragmentary scribe marks visible on opened blaze.