

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Edy., T. 31 S., R. 6 W.

CHAINS

N. 88° 22' W., beginning new measurement.

Ascend 125 ft. over E. slope, changing to NE. slope.

5.20 Dirt road, 10 lks. wide, bears N. 75° W. and S. 75° E.

9.70 Dirt road, 10 lks. wide, bears N. 35° E. and S. 35° W.

20.07 Point for the W 1/16 sec. cor. of secs. 5 and 32.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16  $\frac{S\ 32}{S\ 5}$   
1965

from which

A fir, 8 ins. diam., bears N. 38° W., 30½ lks. dist., mkd. W1/16 S32 BT.

A fir, 13 ins. diam., bears S. 10° E., 28 lks. dist., mkd. W1/16 S5 BT.

Ascend 110 ft. over NE. slope.

29.80 Spur, slopes N.; desc. 245 ft. over W. slope.

38.45 Old water ditch, 6 lks. wide, drains N.

40.14 Point for the cor. of secs. 5, 6, 31, and 32, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S R 6 W  
S 31 | S 32  
S 6 | S 5  
T 31 S  
1965

*FO. OK 7/92  
M. SMALLEY M112-52*

from which

An oak, 10 ins. diam., bears N. 73° E., 36 lks. dist., mkd. T30S R6W S32 BT.

A fir, 8 ins. diam., bears S. 62° E., 26 lks. dist., mkd. T31S R6W S5 BT.

A fir, 18 ins. diam., bears S. 16° W., 28 lks. dist., mkd. T31S R6W S6 BT.

A fir, 15 ins. diam., bears N. 3½° W., 26 lks. dist., mkd. T30S R6W S31 BT.

The corner is located in a ravine, drains N. 65° W.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, pine, madrone, maple, dogwood, yew, chinquapin, alder, oak, live oak, and myrtle; undergrowth, young timber, vine maple, poison oak, salal, oceanspray,

huckleberry, fern, hazel, manzanita, Oregon grape, and blackberry.