

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of N. Edy., T. 31 S., R. 6 W.

CHAINS	
	N. 88° 22' W., bet. secs. 6 and 31.
	Descend 95 ft. over broken NW. slope, across old logged area, through heavy young timber and dense undergrowth.
8.20	Squaw Creek, 1 lk. wide, course N. 10° W.; asc. 125 ft. over NE. slope.
14.50	Spur, slopes N.; desc. 170 ft. over broken NW. slope.
20.07	Point for the E 1/16 sec. cor. of secs. 6 and 31.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$E \frac{1}{16} \frac{S \ 31}{S \ 6}$
	1965
	from which
	A fir, 13 ins. diam., bears N. 14° W., 62 lks. dist., mkd. E 1/16 S31 BT.
	A fir, 23 ins. diam., bears S. 23° W., 41 lks. dist., mkd. E 1/16 S 6 BT.
	Descend 145 ft. over broken NW. slope.
33.60	Enter open meadow, edge bears generally N. and S.
40.14	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 30 S R 6 W
	$\frac{1}{4} \frac{S \ 31}{S \ 6}$
	T 31 S
	1965
	from which
	A pine, 18 ins. diam., bears N. 36½° W., 150 lks. dist., mkd. ¼ S31 BT.
	A maple, 18 ins. diam., bears S. 60° E., 430 lks. dist., mkd. ¼ S 6 BT.
	Descend 20 ft. over NW. slope.
45.00	Enter heavy young timber and dense undergrowth, edge bears generally N. and S.
49.50	Ravine, drains NW.; asc. 85 ft. over NE. slope.
54.40	Spur, slopes N.; desc. 250 ft. over precipitous and broken NW. slope.
60.21	Point for the W 1/16 sec. cor. of secs. 6 and 31.
	Set a brass tablet, 3¼ ins. diam., 3½ ins. stem, in solid rock, with top mkd.
	$W \frac{1}{16} \frac{S \ 31}{S \ 6}$
	1965