

County Surveyor's Record, Douglas County, Oregon

42815

Dependent Resurvey, Portion of N. Bdy., T. 31 S., R. 6 W.

CHAINS

from which

A fir, 10 ins. diam., bears N. 11° W., 19 lks. dist., mkd. W 1/16 S31 BT.

A fir, 10 ins. diam., bears S. 66° E., 26 lks. dist., mkd. W 1/16 S 6 BT.

Descend 110 ft. over NW. slope.

75.50 Rattlesnake Creek, 4 lks. wide, course N.; asc. 160 ft. over E. slope.

82.04 The cor. of Tps. 30 and 31 S., Rs. 6 and 7 W., perpetuated and recorded by John H. Markham, Registered Engineer, in 1961, monumented with an iron pipe, 3/4 in. diam., loosely set, extending 18 ins. above ground, from which the remaining original bearing trees:

A rotted madrone stump, 24 ins. diam., bears N. 36° E., 148 lks. dist., with old axe marks visible on section of blaze. (Record, N. 38° E.)

The rotted remains of a madrone stump, size indeterminate, bears S. 51° W., 27 lks. dist.

A madrone, 16 ins. diam., bears N. 45° W., 212 lks. dist., with opened and burned blaze. (Record, 200 lks.)

and bearing trees marked by Markham

A black oak, 6 ins. diam., bears N. 72° E., 39½ lks. dist., with scribe marks CS visible on partly healed blaze.

A fir, 9 ins. diam., bears South, 81 lks. dist., with healed double blaze.

A fir, 6 ins. diam., bears S. 85° W., 21 lks. dist., with healed double blaze.

A fir, 7 ins. diam., bears N. 15° W., 13½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 30 S
R 7 W R 6 W
S 36 | S 31
S 1 | S 6
T 31 S
1965

from which a new bearing tree

A fir, 15 ins. diam., bears S. 11° E., 76 lks. dist., mkd. T31S R6W S6 BT.

Reset iron pipe alongside the iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, maple, dogwood, yew, pine, chinquapin, alder, oak, live oka, and myrtle; undergrowth young timber, vine maple, poison oak, salal, oceanspray, huckleberry, blackberry, fern, hazel, manzanita, and Oregon grape.