

## County Surveyor's Record, Douglas County, Oregon

Dependnet Resurvey, Portion of N. Bdy., T. 31 S., R. 6 W.

CHAINS

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T.31S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1882 survey by William H. Byars.)

From the cor. of secs. 4, 5, 8 and 9, occupied by the  
rotted and burned remains of the original fir corner  
tree, from which the original bearing trees:

The rotted remains of a madrone stump, size  
indeterminate, bears N. 35° E., 50 lks. dist.

~~— ROTTED REMAINS MADRONE STUMP, S. 45° E. 7 lks.~~

A burned madrone, 33 ins. diam., bears S. 58° W.,  
107 lks. dist., no marks remaining.  
(Record 115 lks.)

A madrone, 27 ins. diam., bears N. 68° W., 47 lks.  
dist., with old axe marks visible in reverse  
on burned overgrowth. (Record, 45 lks.)

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.  
in the ground, in the center of the shell of the  
original corner tree, with brass cap mkd.

T 31 S R 6 W  
S 5 | S 4  
S 8 | S 9  
1965

from which new bearing trees

A fir, 17 ins. diam., bears N. 48° E., 62 lks.  
dist., mkd. T31S R6W S4 BT.

A fir, 30 ins. diam., bears S. 74½° E., 75 lks.  
dist., mkd. T31S R6W S9 BT.

A fir, 8 ins. diam., bears S. 66° W., 36 lks.  
dist., mkd. T31S R6W S8 BT.

A fir, 23 ins. diam., bears N. 12° W., 46 lks.  
dist., mkd. T31S R6W S5 BT.

N. 1° 30' E., bet. secs. 4 and 5, marking and blazing the  
true line.

Descend 15 ft. over N. slope, through heavy timber and  
dense undergrowth.

0.35 Ravine, drains N. 60° W.; asc. 75 ft. over SW. slope.  
4.00 Spur, slopes W.; desc. 230 ft. over NW. slope.  
9.80 Ravine, drains N. 60° W.; asc. 70 ft. over SW. slope.  
13.70 Spur, slopes N. 60° W.; desc. 265 ft. over NW. slope.  
27.40 Ravine, drains W.; asc. 70 ft. over SW. slope.