

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS

- 30.00 Spur, slopes W.; desc. 180 ft. over NW. slope.
- 36.00 Enter logged area with scattering timber and dense undergrowth, edge bears generally N. 30° E. and S. 30° W.
- 36.50 Gravelled road, 30 lks. wide, bears N. 30° E. and S. 30° W.
- 39.14 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, perpetuated and recorded by R. H. Gee, Registered Engineer, in 1954, from an original bearing tree which is no longer in existence, monumented with an iron pipe, $\frac{3}{4}$ in diam., firmly set, extending 4 ins. above ground, from which bearing trees marked by Gee:
- A fir, 16 ins. diam., bears S. 48° E., 10 lks. dist., with illegible scribe marks visible on partly healed double blaze.
- A fir, 16 ins. diam., bears N. 33° W., 5 lks. dist., with healed double blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, over local iron pipe, to bedrock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
- T 31 S R 6 W

1

S 5 | S 4

1965
-
- N. 0° 02' W., beginning new measurement.
- Descend 300 ft. over broken NW. slope.
- 17.80 Ravine, drains W.; asc. 90 ft. over SW. slope.
- 22.25 Spur, slopes W.; desc. 175 ft. over NW. slope.
- 28.80 Gravelled road, 20 lks. wide, bears NE. and SW.
- 29.50 Council Creek, 8 lks. wide, course N., from SW.; desc. 3 ft. along creek bottom.
- 31.20 Leave creek, course NE.; asc. 10 ft. along broken E. slope.
- 41.65 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Twp.
- Land, mountainous.
Soil, rocky clay loam.
Timber, fir, cedar, madrone, maple, dogwood, yew, pine, chinquapin, alder, oak, live oak, and myrtle; undergrowth, young timber, vine maple, poison oak, salal, fern, oceanspray, manzanita, Oregon grape, huckleberry, and blackberry.
-
- From the cor. of secs. 4, 5, 8 and 9.
- N. 89° 21' W., bet. secs. 5 and 8