

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS

Ascend 10 ft. along N. slope, through heavy timber and dense undergrowth.

1.40 Top of ascent, slopes N.; desc. 660 ft. over NW. slope.

13.10 Gravelled road, 20 lks. wide, bears N. 60° E. and S. 60° W.

28.40 Council Creek, 8 lks. wide, course N. 18° W.; asc. 395 ft. over E. slope, changing to SE. slope.

39.96 The  $\frac{1}{4}$  Sec. cor. of secs. 5 and 8, monumented with a wooden stake, 3 ins. square, firmly set, extending 36 ins. above ground, from which the original bearing trees:

The rotted remains of a madrone stump, 38 ins. diam., bears North, 47 lks. dist., slope dist., 54 lks., no marks remaining. (Record, 54 lks.)

A madrone, 14 ins. diam., bears S. 28° E., 26 lks. dist., with old opened blaze, no marks remaining.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 23 ins. in the ground, with brass cap mkd.

T 31 S R 6 W

$\frac{1}{4}$   $\frac{S 5}{S 8}$

1965

from which new bearing trees

A fir, 22 ins. diam., bears N. 39° W., 51 lks. dist., mkd.  $\frac{1}{4}$  S5 BT.

A fir, 12 ins. diam., bears S. 49 $\frac{1}{2}$ ° W., 37 lks. dist., mkd.  $\frac{1}{4}$  S8 BT.

N. 89° 29' W., beginning new measurement.

Ascend 10 ft. over SE. slope.

2.20 Ravine, drains SE.; asc. 440 ft. over broken SE. slope.

2.40 Old water ditch, 6 lks. wide, drains N. 28° W.

28.00 Spur, slopes S. 10° E.; desc. 55 ft. over SW. slope.

30.60 Ravine, drains S. 20° E., asc. 180 ft. over broken SE. slope.

35.65 Old water ditch, 6 lks. wide, drains N. 8° W.

39.90 Ravine, drains SE.; asc. 20 ft. over NE. slope.

40.57 The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron post, 1 in. diam., firmly set, extending 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS

T 31 S

$\frac{S 6}{S 7}$   $\frac{S 5}{S 8}$

R 6 W

1965

OFFICE