

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS

from which the remaining original bearing trees:

A madrone stump, 10 ins. diam., bears N. 50° E.,
29 lks. dist., no marks remaining.

A fir, 50 ins. diam., bears S. 36° E., 37 lks.
dist., with illegible scribe marks visible on
old opened blaze.

A madrone, 27 ins. diam., bears N. 16° W., 37 lks.
dist., with old opened blaze; has been remarked
S6 CS BT on lower blaze.

and bearing trees marked by Byron

A fir, 8 ins. diam., bears N. 52½° E., 66 lks.
dist., with illegible scribe marks visible on
partly healed double blaze.

A fir, 10 ins. diam., bears S. 13° W., 79 lks.
dist., with illegible scribe marks visible on
partly healed double blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, madrone, maple, dogwood, yew, pine, chnquapin,
alder, oak, & live oak; undergrowth, young timber, vine maple,
poison oak, salal, fern, oceanspray, manzanita, Oregon grape,
huckleberry, and blackberry.

N. 1° 07' E., bet. secs. 5 and 6.

Descend 5 ft. over NE. slope, through heavy timber and
dense undergrowth.

0.65 Ravine, drains SE.; asc. 180 ft. over SE. slope.

10.40 Jeep road, 10 lks. wide, bears N. 35° E. and S. 35° W.

13.00 Spur, ridge, bears NE. and SW.; desc. 90 ft. over broken NW. slope.

20.09 Point for the S 1/16 sec. cor. of secs. 5 and 6.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.

S 1/16
S 6 | S 5
1965

from which

A fir, 25 ins. diam., bears N. 66° E., 75 lks.
dist., mkd. S1/16 S5 BT.

A fir, 18 ins. diam., bears S. 59½° W., 67 lks.
dist., mkd. S1/16 S6 BT.

Descend 155 ft. over NW. slope.

26.35 Jeep road, 10 lks. wide, bears SE. and NW., curving to NE.

26.95 Same jeep road, bears SW. and NE., curving to N. 10° W.

28.40 Same jeep road, bears S. 10° E. and N. 10° W., curving to NE.

29.35 Same jeep road, bears SW. and NE., curving to N. 20° W.