

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS 30.00	Same jeep road, bears N. 20° W. and S. 20° E.; also spur ridge, bears N. 10° W. and S. 10° E.; desc. 230 ft. over NE. slope.
31.94	Old water ditch, 6 lks. wide, drains N. 70° W.
40.18	Point for the $\frac{1}{4}$ Sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 31 S R 6 W S 6 S 5 1965 </div> from which A fir, 10 ins. diam., bears N. 59° E., 60 lks. dist., mkd. $\frac{1}{4}$ S5 BT. A fir, 15 ins. diam., bears N. 71° W., $29\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S6 BT. Descend 55 ft. over NE. slope.
43.00	Head of ravine, drains E.; asc. 165 ft. over SE. slope.
51.60	Jeep road, 10 lks. wide, bears N. 65° E. and S. 35° W.
52.75	Spur ridge, bears N. 20° E. and S. 20° W., desc. 110 ft. over NW. slope.
60.27	Point for the N $\frac{1}{16}$ sec. cor. of secs. 5 and 6. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> N $\frac{1}{16}$ S 6 S 5 1965 </div> from which A fir, 40 ins. diam., bears S. 82° E., 37 lks. dist., mkd. N $\frac{1}{16}$ S5 BT. A fir, 18 ins. diam., bears S. 62° W., 13 lks. dist., mkd. N $\frac{1}{16}$ S6 BT. Descend 250 ft. over NW. slope.
71.20	Ravine, drains N. 70° W.; asc. 55 ft. over SW. slope.
75.50	Spur, slopes S. 75° W.; desc. 150 ft. over NW. slope. changing to N. slope.
80.13	Old water ditch, 6 lks. wide, drains S. 80° E.
81.73	The cor. of secs. 5, 6, 31 and 32.

Land, mountainous.
 Soil, rocky clay loam.
 Timber, fir, cedar, madrone, maple, dogwood, yew, pine, chinquapin, live oak, and alder; undergrowth, vine maple, young timber, poison oak, salal, fern, oceanspray, manzanita, Oregon grape, huckleberry, and blackberry.