

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 6 W.

CHAINS	Subdivision of Section 5, T. 31 S., R. 6 W., Willamette Meridian, Oregon
	From the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
	N. $0^{\circ} 46'$ E., on the N. and S. center line of sec. 5.
	Ascend 110 ft. over SE. slope, across old logged area, through heavy young timber and dense undergrowth.
0.28	Old water ditch, 6 lks. wide, drains E.
5.25	Spur, slopes S. 70° E.; desc. 40 ft. over NE. slope.
7.85	Ravine, drains S. 70° E.; asc. 95 ft. over SE. slope.
14.50	Spur, slopes E.; desc. 465 ft. over NE. slope.
39.60	Point for the center $\frac{1}{4}$ sec. cor. of sec. 5, at intersection with the E. and W. center line.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 31 S R 6 W C $\frac{1}{4}$ S 5 1965
	from which
	An oak, 9 ins. diam., bears S. 35° E., 12 lks. dist., mkd. C $\frac{1}{4}$ S 5 BT.
	A fir, 30 ins. diam., bears N. 85° W., 39 lks. dist., mkd. C $\frac{1}{4}$ S 5 BT.
	Descend 105 ft. over NE. slope, changing to N. slope.
44.15	Creek, 2 lks. wide, course N. 80° E.; asc. 190 ft. over general S. slope.
59.14	Wire fence, bears E. and W.
59.49	Point for the center N $1/16$ sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	C N $1/16$ S 5 C 1965
	from which
	A fir, 10 ins. diam., bears N. 40° E., 16 lks. dist., mkd. C N $1/16$ S 5 BT.
	An oak, 13 ins. diam., bears S. 46° W., 53 lks. dist., mkd. C N $1/16$ S 5 BT.
	Ascend 180 ft. over S. slope, changing to SE. slope.
62.67	Dirt road, 10 lks. wide, bears N. 68° E. and S. 68° W.
67.80	Same road, bears N. 60° E. and S. 5° W.
69.70	Old water ditch, 6 lks. wide, drains N. 35° E.
72.30	Top of ascent, slopes E.; desc. 50 ft. over N. slope.