

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 5, T. 31 S., R. 6 W.

CHAINS	
78.85	Dirt road, 10 lks. wide, bears N. 60° W. and S. 60° E.
80.93	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the N. bdy. of the Twp.
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	N. 88° 42' W., on the E. and W. center line of sec. 5.
	Descend 325 ft. over NW. slope, changing to W. slope, across old logged area, through scattering young timber & dense undergrowth.
16.55	Dirt road, 10 lks. wide, bears N. 50° E. and S. 50° W.
18.55	Council Creek, 8 lks. wide, course N. 25° E.; asc. 230 ft. over broken NE. slope.
21.12	Old water ditch, 6 lks. wide, drains N. 20° W.
40.43	The center $\frac{1}{4}$ sec. cor. of sec. 5.
	Ascend 30 ft. over broken NE. slope.
41.00	Leave logged area, enter old growth timber, edge bears generally N. and S.
53.90	Creek, 1 lk. wide, course N. 75° E.; asc. 5 ft. over SE. slope.
55.25	Same creek, course S. 55° E.; asc. 190 ft. over NE. slope.
60.63	Point for the center S $\frac{1}{16}$ sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{W } \frac{1}{16} \\ \text{C } \quad \text{S } \frac{1}{5} \quad \text{C} \\ 1965 \end{array}$
	from which
	A fir, 12 ins. diam., bears N. 75° E., $47\frac{1}{2}$ lks. dist., mkd. C W $\frac{1}{16}$ S $\frac{1}{5}$ BT.
	A fir, 38 ins. diam., bears S. $24\frac{1}{2}$ ° E., 50 lks. dist., mkd. C W $\frac{1}{16}$ S $\frac{1}{5}$ BT.
	Ascend 325 ft. over broken NE. slope.
63.63	Old water ditch, 6 lks. wide, drains N. 60° W.
80.83	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6
	From the center W $\frac{1}{16}$ sec. cor. of sec. 5.
	N. 0° 57' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 5.
	Descend 50 ft. over NE. slope, through heavy timber and dense undergrowth.
5.05	Creek, 1 lk. wide, course S. 60° E.; asc. 150 ft. over SE. slope.
10.95	Old water ditch, 6 lks. wide, drains S. 85° E.
19.41	Woven wire fence, bears E. and W.
19.98	Point for the NW $\frac{1}{16}$ sec. cor. of sec. 5, at intersection with the E. and W. center line of the NW $\frac{1}{4}$.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.