

## County Surveyor's Record, Douglas County, Oregon

T. 31 S., R. 3 W.

CHAINS

The history of surveys in that portion of township 31 south, range 3 west, Willamette Meridian, Oregon, covered by this survey is as follows:

William M. Bushey surveyed that portion of the subdivisional lines in 1894.

The resurvey was made at the request of the Roseburg District Manager for administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original survey are retraced and search is made for all corners and other calls of the record. Identified corners are remonumented in their original positions, lost corners are reestablished and remonumented at proportionate positions based on the original record. The retracement data are thoroughly verified and only the true line field notes are given herein. Only the lines bounding or crossing public lands are blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated July 22, 1964, under Group No. 555, Oregon.

The directions of the lines were determined by the solar transit method.

The geographic position of the corner of sections 10, 11, 14 and 15, as scaled from the Days Creek Quadrangle Map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude 42° 53.1' N. Longitude 123° 01.9' W.

The mean magnetic declination is 19° 18' E.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the 1894 survey by William M. Bushey)

The cor. of secs. 10, 11, 14, and 15, recorded and remonumented by J. H. Markham, Jr., registered Professional Engineer, in 1959, with an iron pipe, 3/4 in. diam., 4 ins. above the ground, firmly set, subsequently remonumented by Milo E. Godfrey, Deputy County Surveyor, in 1964, with an iron pipe, 1 in. diam., 12 in. above the ground, firmly set, with brass cap mkd.

## COUNTY SURVEYORS OFFICE

T 31 S  
S 10 | S 11  
S 15 | S 14  
R 3 W  
1964

from which the original bearing trees

A madrone, 14 ins. diam., bears N. 49½° E., 48½ lks. dist., with scribe marks S11 R3W BT and other illegible marks visible on bark blaze.  
(Record distance, 47½ lks.)