

47 12225  
 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 3 W.

CHAINS

A fir, 40 ins. diam., bears S. 41° E., 58 lks. dist., with illegible scribe marks visible on opened blaze.

A down fir, 24 ins. diam., bears S. 33½° W., 22 lks. dist., with healed double blaze.

A shell of a Fir Stump, 36 ins. diam., bears N. 39½° W., 9 3/4 lks. dist.

and bearing trees marked by Markham

A madrone, 11 ins. diam., bears N. 15° E., 8½ lks. dist., with scribe marks T31S R3W S11 CS BT visible on new blaze. (Was remarked by Godfrey in 1964)

A live oak, 6 ins. diam., bears S. 37° E. 42½ lks. dist., with scribe marks S BT visible on partially healed double blaze.

A pine, 6 ins. diam., bears S. 5° E. 33½ lks. dist., with scribe marks S BT visible on partially healed double blaze.

A chinquapin, 5 ins. diam., bears S. 86° W., 16 lks. dist., with scribe marks S15 BT visible on partially healed double blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 48° W., 91½ lks. dist., mkd. T31S R3W S10 BT.

Add marks ELM 1964 to bottom of brass Cap.

N. 0° 49' W., bet. secs. 10 and 11, marking and blazing the true line.

Descend 195 ft. over NW. slope, changing to N. slope, through heavy timber and dense undergrowth.

6.30 Creek, 6 lks. wide, course W.; asc. 685 ft. over S. slope, changing to SE. slope.

37.85 The original line tree marked by William M. Bushey, in 1894, a fir, 39 ins. diam., marked with 2 notches on N. and S. sides.

N. 0° 26' W., beginning new measurement.

Ascend 25 ft. over SE. slope.

2.02 Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 3 W  
 ¼  
 S 10 | S 11  
 1964

from which