

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 3 W.

CHAINS

A fir, 21 ins. diam., bears S. 38 3/4° E., 57 lks. dist., mkd. 1/4 S11 BT.

A fir, 15 ins. diam., bears N. 32° W., 31 lks. dist., mkd. 1/4 S10 BT.

Corner is located on a spur, slopes S. 60° W.

Descend 160 ft. over NW. slope.

6.40 Ravine, drains W.; asc. 55 ft. over SW. slope.

9.20 Spur, slopes W.; desc. 100 ft. over NW. slope.

12.70 Ravine, drains N. 60° W.; asc. 230 ft. over SW. slope.

22.00 Spur ridge, bears N. 10° W. and S. 40° E.; desc. 320 ft. over NE. slope.

35.12 The original line tree marked by William M. Bushey, in 1894, a cedar, 60 ins. diam., marked with 2 notches on N. and S. sides.

N. 0° 26' W., beginning new measurement.

Descend 165 ft. over NE. slope.

7.79 The cor. of secs. 2, 3, 10 and 11, recorded and remonumented by J. H. Markham, Jr., Registered Professional Engineer, in 1959, with a wood stake, 2 ins. square, 48 ins. above the ground, firmly set, subsequently remonumented by M. E. Godfrey, Deputy County Surveyor, in 1964, with an iron pipe, 1 in. diam., 14 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S	
S 3	S 2
S 10	S 11
R 3 W	
1964	

from which the remaining original bearing trees

A cedar, 13 ins. diam., bears S. 25 1/4° E., 38 1/2 lks. dist., with scribe marks 3W S11 visible on opened blaze. (Record distance, 36 1/2 lks.)

A cedar, 31 ins. diam., bears S. 63 3/4° W., 42 1/2 lks. dist., with a healed blaze.

A down and rotted fir, size indeterminate, bears N. 59° W., 18 1/4 lks. dist.

and bearing trees marked by Markham

A chinquapin, 16 ins. diam., bears N. 16° E., 93 lks. dist., with scribe marks R3W 31 S visible on partially healed blaze.

A fir, 6 ins. diam., bears S. 62° E., 5 3/4 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 6 ins. diam., bears S. 84° W., 23 lks. dist., with illegible scribe marks visible on partially healed double blaze.