

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 3 W.

CHAINS	
	<p>A fir, 10 ins. diam., bears N. 10° W., 50 lks. dist., with scribe mark S visible on partially healed double blaze.</p> <p>Add marks HLM 1964 to bottom of brass cap.</p> <p>Corner is located at the SW. corner of a logged area.</p> <p>Land, mountainous. Soil, rocky clay, loam. Timber, fir, cedar, hemlock, chinquapin, alder, madrone, dogwood, live oak, maple, pine, and yew; undergrowth, vine maple, salal, Oregon grape, fern, hazel, ocean spray, poisonoak, huckleberry, blackberry, rhododendron, and manzanita.</p>
	<p>From the corner of secs. 10, 11, 14 and 15.</p> <p>S. 89° 51' W., bet. secs. 10 and 15.</p> <p>Descend 80 ft. over W. slope, through heavy timber and dense undergrowth.</p>
1.60	Ravine, drains NW.; asc. 20 ft. over NE. slope.
2.60	Ravine, drains N. 20° E.; asc. 100 ft. over NE. slope.
6.10	Spur, slopes N.; desc. 60 ft. over NW. slope.
8.50	Ravine, drains N.; asc. 60 ft. over NE slope.
10.60	Spur, slopes N.; desc. 55 ft. over NW. slope.
13.30	Ravine, drains N.; asc. 65 ft. over NE slope.
18.20	Spur, slopes NW.; desc. 325 ft. over general W. slope.
26.60	East Fork of Stouts Creek, 10 lks. wide, course N. 20° E.; asc. 370 ft. over NE. slope.
39.93	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 15, monumented with the original basalt stone, 10 x 10 x 5 ins., loosley set, 5 ins. in the ground, marked <math>\frac{1}{4}</math> on N. face, from which the remains of the original bearing trees:</p> <p>A down and rotted madrone, 10 ins. diam., bears N. 20° W., 18 lks., with fragmentary scribe marks visible on fragments of overgrowth, tree has been displaced and original position is indeterminate. (Record bearing and distance, S. 86<math>\frac{1}{2}</math>° W., 33<math>\frac{1}{2}</math> lks.)</p> <p>A down and rotted madrone, 10 ins. diam., bears N. 87° W., 31 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record distance, 33<math>\frac{1}{2}</math> lks.)</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p>T 31 S R 3 W</p> <p><math>\frac{1}{4}</math> <math>\frac{S 10}{S 15}</math></p> <p>1964</p>