

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 3 W.

CHAINS

N. 0° 14' E., bet. secs. 9 and 10.

Ascend 20 ft. over SW. slope, through heavy timber and dense undergrowth.

1.00 Spur, slopes W.; desc. 20 ft. over NW.slope.

3.00 Ravine, drains W.; asc. 25 ft. over SW. slope.

7.00 Spur, slopes N. 80° W.; desc. 135 ft. over NW. slope.

11.00 Ravine, drains S. 80° W.; asc. 235 ft. over SW. slope.

19.00 Spur, slopes S. 60° W.; desc. 35 ft. over NW. slope.

23.40 Ravine, drains S. 60° W.; asc. 60 ft. over S. slope.

25.90 Spur, slopes SW.; desc. 40 ft. over NW.slope.

32.15 Creek, 1 lk. wide, course SW.; asc. 195 ft. over S. slope.

40.34 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, recorded and remonumented by M. E. Godfrey, Deputy County Surveyor, in 1964, with an iron pipe, 1 in. diam., 12 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T	31	S
S		S
$\frac{1}{4}$	9	10
R	3	W
1964		

from which the original bearing trees

A cedar, 33 ins. diam., bears N. 33 $\frac{1}{2}$ ° E., 37 lks. dist., with scribe marks $\frac{1}{4}$ S visible on opened blaze. (Record distance, 29 lks.)

A cedar, 33 ins. diam., bears N. 43 $\frac{1}{2}$ ° W., 29 lks. dist., with scribe marks $\frac{1}{4}$ S visible on opened blaze. (Record distance, 37 lks.)

and a bearing tree marked by Godfrey

A madrone, 12 ins. diam., bears N. 86 $\frac{1}{2}$ ° W., 32 lks. dist., with scribe marks $\frac{1}{4}$ S 9 CS BT visible on on new double blaze.

Add marks BLM 1964 to bottom of brass cap.

N. 0° 56' W., beginning new measurement.

Ascend 110 ft. over S. slope, changing to SW. slope.

5.60 Spur, slopes S. 60° W.; desc. 35 ft. over NW. slope.

8.00 Ravine, drains S. 75° W.; asc. 275 ft. over broken SW. slope.

23.90 Spur, slopes W.; desc. 5 ft. over NW. slope.

24.79 The original line tree marked by William M. Bushey, in 1894, a dead fir, 34 ins. diam., marked with 2 notches on N. and S. sides.