

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 31 S., R. 3 W.

CHAINS

From the corner of secs. 2, 3, 10 and 11.

S. 89° 20' W., bet. secs. 3 and 10.

Ascend 145 ft. over broken NE. slope, through heavy timber and dense undergrowth.

5.30 Spur ridge, bears N. 10° W. and S. 10° E.; desc. 680 ft. over general W. slope.

22.30 East Fork of Stouts Creek, 10 lks. wide, course N. 10° E.; asc. 640 ft. over general E. slope.

34.70 Spur, slopes N. 60° E.; asc. 70 ft. over NE. slope.

39.16 The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, determined at record distance from the original bearing trees:

A madrone clump, bears N. 89° W., 74 lks. dist. (Record bearing, N. 86° W.)

A madrone, 26 ins. diam., bears South, 71 $\frac{1}{2}$  lks. dist., with scribe marks & BT visible on opened blaze.

At the corner point

Set and iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 3 W  
 $\frac{1}{4}$   $\frac{S \ 3}{S \ 10}$   
 1964

from which new bearing trees

A fir, 19 ins. diam., bears N. 70° E. 6 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S 3 BT.

A fir, 15 ins. diam., bears S. 38 $\frac{1}{2}$ ° W., 21 lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

S. 89° 59' W., beginning new measurement.

Ascend 105 ft. over NE. slope.

5.30 Spur, slopes S. 70° E.; asc. 430 ft. over SE. slope.

25.00 Ridge, bears N. 30° E. and S. 30° W.; desc. 455 ft. over NW. slope.

40.16 The corner of secs. 3, 4, 9 and 10.

Land, mountainous.  
 Soil, rocky clay loam.  
 Timber, fir, hemlock, cedar, chinquapin, madrone, alder, dogwood, live oak, maple, pine and yew;  
 Undergrowth, vine maple, salal, fern, Oregon grape, hazel, ocean spray, poison oak, huckleberry, blackberry, rhododendron.