

# County Surveyor's Record, Douglas County, Oregon

12836

13

T. 33 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The history of surveys of township 33 south, range 6 west, Willamette Meridian, Oregon, in the portion of the township covered by the resurvey, is as follows:

The west boundary was surveyed by Wells Lake and George W. Hyde in 1855. The subdivisinal lines were surveyed by William H. Byars in 1882, as shown upon the plat approved June 16, 1882.

The resurvey and subdivision-of-section survey was made at the request of the Medford District Manager for the administrative purposes of the Bureau of Land Management.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions, lost corners were reestablished and remonumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only lines bounding or crossing public lands were blazed.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 8, 1963 and May 3, 1957, under Group Nos. 526 and 350, Oregon.

The directions of lines were determined by deflection angles from direct solar observations.

The geographic position of the southeast corner of section 7, as scaled from the Glendale Quadrangle map, prepared by the United States Geological Survey, in 1954, is as follows:

Latitude 42° 42.6' N.      Longitude 123° 26.6" W.

The mean magnetic declination is 20° E.

Dependent Resurvey of a Portion of the West Boundary,  
T. 33 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the 1855 survey by Wells Lake and George W. Hyde)

Beginning at the  $\frac{1}{4}$  sec.cor. of secs. 13 and 18, on the W. bdy. of the Tp., determined from the original bearing trees:

A Douglas fir, dead and down, 22 ins. diam., bears N. 80° E., 24 lks. dist., mkd.  $\frac{1}{4}$  S BT on opened blaze.

A Douglas fir, 40 ins. diam., bears N. 52° W., 32 lks. dist., mkd.  $\frac{1}{4}$  S on opened blaze.  
(Record, 26 lks.)

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.