

12237
 County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 33 S., R. 6 W.

CHAINS

S 13	↑	S 18
R 7 W		R 6 W
T 33 S		
1963		

from which

A Douglas fir, 6 ins. diam., bears S. 72° E.,
 140 lks. dist., mkd. $\frac{1}{4}$ S18 BT.

A Douglas fir, 10 ins. diam., bears S. 78° W.,
 74 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

N. 0° 06' E., bet. secs. 13 and 18, marking and blazing
 the true line.

Descend 330 ft. over NE. slope.

8.30 Creek, 3 lks. wide, course N. 40° W.; asc. 35 ft. over
 SW. slope.

16.90 Spur, slopes W.; desc. 45 ft. over NW. slope.

20.33 Point for the N 1/16 sec. cor. of secs. 13 and 18.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins.
 in the ground with brass cap mkd.

N 1/16		
S 13		S 18
1964		

from which

A chinquapin, 6 ins. diam., bears S. 80° E.,
 20 lks. dist., mkd. N 1/16 S18 BT.

A Douglas fir, 8 ins. diam., bears S. 49° W.,
 38 lks. dist., mkd. N 1/16 S13 BT.

Descend 195 ft. over NW. slope.

24.30 Battlesnake Creek, 5 lks. wide, course N. 70° W., asc.
 50 ft. over SW. slope.

26.20 Road, gravelled, 20 lks. wide, bears N. 85° W. and
 S. 85° E., asc. 415 ft. over S. slope.

39.10 Spur, slopes S. 50° W.; desc. 35 ft. over NW. slope.

40.66 Point for the cor. of secs 7, 12, 13 and 18, at pro-
 portionate distance; there is no remaining evidence of
 the original corner.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T 33 S		
R 7 W		R 6 W
S 12		S 7
S 13		S 18
1963		

from which

A Douglas fir, 12 ins. diam., bears N. 39° E.,
 83 lks. dist., mkd. T33S R6W S 7 BT.