

County Surveyor's Record, Douglas County, Oregon

15

Dependent Resurvey, Portion of W. Bdy., T. 33 S., R. 6 W.

CHAINS

A ponderosa pine, 38 ins. diam., bears S. 34° E.,
98 lks. dist., mkd. T33S R6W S18 BT.

A Douglas fir, 4 ins. diam., bears S. 57° W.,
36 lks. dist., mkd. XBT.

A chinquapin, 6 ins. diam., bears N. 44° W.,
90 lks. dist., mkd. T33S R7W S12 BT.

Land, mountainous.
Soil, rocky clay.
Timber, Douglas fir, and scattering ponderosa pine;
Undergrowth, vine maple, arrowwood, and poison oak.

N. 0° 06' E., bet. secs. 7 and 12.

Descend 30 ft. over NW. slope.

1.50 Ravine, drains S. 40° W.; asc. 45 ft. over SE. slope,
changing to S. slope/

6.50 Spur slopes W.; desc. 50 ft. over NW. slope.

19.60 Ravine, drains S. 75° W.; asc. 240 ft. over SW. slope.

31.65 Ridge, bears N. 60° W. and S. 60° E.; desc. 285 ft.
over N. slope, changing to NW. slope.

40.66 The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, determined from the remains of
the original bearing trees:

A Douglas fir snag, 40 ins. diam., bears
N. 45° E., 19 lks. dist., mkd. $\frac{1}{4}$ S BT on opened
blaze. (Record, N. 35° E.)

A Douglas fir snag, 30 ins. diam., bears
N. 32° W. 41 lks. dist., mkd. $\frac{1}{4}$ S BT. on
opened blaze.

At the corner point

Set an iron post, 30 ins. long 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, and in a mound of stone, 4 ft., base
to top, with brass cap mkd.

$\frac{1}{4}$
 S 12 | S 7
 R 7 W | R 6 W
 T 33 S
 1963

from which

A Douglas fir snag, 36 ins. diam., bears
N. 52° E., 33 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.

A Douglas Fir snag, 40 ins. diam., bears
S. 14° W., 130 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

There are no suitable live bearing trees available within limits.

N. 0° 11' E., beginning new measurement.

Descend 250 ft. over NW. slope.

6.90 Creek, 2 lks. wide, course N. 30° E.; asc. 5 ft. over E. slope.