

County Surveyor's Record, Douglas County, Oregon

Dependant Resurvey, Subdivisional Lines, T. 33 S., R. 6W.

CHAINS

from which the remains of the original bearing trees

A Douglas fir snag, 30 ins. diam., bears N. 46° E., 22 lks. dist., with no marks remaining.

A madrone snag, 16 ins. diam., bears S. 25° E., 22 lks. dist., with a rotted blaze.

A stump hole, bears S. 78° W., 56 lks. dist.

A Douglas fir snag, 34 ins. diam., bears N. 52° W., 29 lks. dist., with no marks remaining.

and bearing trees marked by the County Surveyor

A Douglas fir, 5 ins. diam., bears N. 29° E., 31 lks. dist., mkd. S 8 CS BT.

A chinquapin, 6 ins. diam., bears S. 7° E., 12 lks. dist., mkd. S17 T33S R6W CS BT.

A madrone, 12 ins. diam., bears S. 75° SW., 53 lks. dist., mkd. S18 T33S R6W CS BT.

A Douglas fir, 3 ins. diam., bears N. 70° W., 30 lks. dist., mkd. CS BT.

S. 87° 00' W., bet. secs. 7 and 18, marking and blazing the true line.

Descend 215 ft. over NW. slope.

- 7.25 Road, dirt, 25 lks. wide, bears N. 15° E. and S. 15° W.; desc. 30 ft. over NW. slope.
- 8.00 Ravine, drains N. 30° W.; asc. 140 ft. over NE. slope.
- 11.35 Spur, slopes N. 10° E.; desc. 15 ft. over NW. slope.
- 12.30 Ravine, drains N 15° W.; asc. 30 ft. over NE. slope.
- 14.25 Spur, slopes N.; desc. 95 ft. over NW. slope.
- 18.80 Ravine, drains N. 10° W.; asc. 20 ft. over NE. slope.
- 21.90 Spur, slopes N. 15° W.; desc. 30 ft. over NW. slope.
- 22.90 Creek, 1 lk. wide, course N. 20° W.; asc. 50 ft. over NE. slope.
- 23.60 Spur, slopes N. 30° W.; desc. 5 ft. over NW. slope.
- 24.50 Creek, 3 lks. wide, course N. 70° E.; asc. 490 ft. over SE. slope, changing E. slope.
- 41.36 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 33 S R 6 W
 $\frac{1}{4}$ $\frac{S 7}{S 18}$
 1964

from which