

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 33 S., R. 6 W.

CHAINS

$\frac{1}{4}$
 S 7 | S 8
 T 33 S R 6 W
 1964

FPOK BY
 G N49100
 3/94 M118-79

from which

A Douglas fir, 8 ins. diam., bears S. 75° E.,
44 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.

A Douglas fir, 6 ins. diam., bears N. 79° W.,
10 lks. dist., mkd. $\frac{1}{4}$ S 7 BT.

Ascend 55 ft. over SE. slope.

47.15 Spur, slopes E.; desc. 130 ft. over NE. slope.

55.35 Creek, 4 lks. wide, course S. 65° E.; asc. 50 ft. over
SW. slope.

57.21 Point for the N 1/16 sec. cor. of secs. 7 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in
the ground, with brass cap mkd.

N 1/16
 S 7 | S 8
 1964

FPOK BY
 G N49100
 3/94 M118-79

from which

A Douglas fir, 14 ins. diam., bears S. 66° E.,
92 lks. dist., mkd. N 1/16 S 8 BT.

A Douglas fir, 14 ins. diam., bears N. 9° W.,
111 lks. dist., mkd. N 1/16 S 7 BT.

Ascend 55 ft. over s SE. slope.

60.80 Spur, slopes N. 40° E.; desc. 185 ft. over NW. slope.

69.80 Creek, 2 lks. wide, course N. 35° E.; asc. 10 ft. over
SE. slope.

70.50 Creek, 2 lks. wide, course S. 70° E.; asc. 100 ft. over
SE. slope.

74.40 Spur, slopes S. 80° E.; desc. 60 ft. over NE. slope.

76.28 The cor. of secs. 5, 6, 7 and 8, remonumented by the
Douglas County Surveyor, in 1963, from an original
bearing tree, with an iron post, 1½ ins. diam., firmly
set, protruding 12 ins. above the ground, with brass cap
mkd.

COUNTY SURVEYORS OFFICE
 1963 S 6 | S 5 T 33 S
 S 7 | S 8 R 6 W

from which an original bearing tree

A madrone stump, size indeterminate, bears
S. 10° W., 10 lks. dist., mkd. S on rotted blaze.

and bearing trees marked by the County Surveyor

A Douglas fir, 10 ins. diam., bears S. 80° E.,
117 lks. dist., mkd. S8 T33S R6W CS BT.